

TONER CONCENTRATE-VERSATEC

MSDS Number

BBCSM

National Stock Number

6850-00D000459

Product Name

TONER CONCENTRATE-VERSATEC

Manufacturer

SUNFAX MANUFACTURING INC

Product Identification

Product ID:TONER CONCENTRATE-VERSATEC

MSDS Date:01/01/1985

FSC:6850

NIIN:00D000459

MSDS Number: BBCSM

Responsible Party

SUNFAX MANUFACTURING INC

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: DO987

Contractor

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

MIXED ISODECANES

Fraction By Weight: 80.0%

ACGIH TLV: 300 PPM

First Aid

First Aid:INHAL:REMOVE FROM SOLVENT LADEN AREA TO FRESH AIR
AREA.ACCIDENTAL INGEST:DO NOT INDUCE VOMITING; CALL DR
IMMEDIATELY.EYES:FLUSH W/WATER FOR 15 MINUTES.IF IRRITATION
PERSISTS,CALL DR.

Fire Fighting

Flash Point:102-107F TCC

Lower Limits:0.8

Upper Limits:7.0

Extinguishing Media:FOAM-TYPE EXTINGUISHERS-SUPERIOR TO CO*2
EXTINGUISHERS

Fire Fighting Procedures:AVOID WATER-IT TENDS TO SPREAD HYDROCARBON
SOLVENT FIRES.

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES. IF AMOUNT IS SMALL (UNDER 1 PT) ALLOW TO EVAPORATE INCREASING AIR CIRCULATION IF POSSIBLE & AVOID ANY SPARKS OR OPEN FLAMES. IF AMOUNT IS LARGE, TRY TO CONTAIN & MOP UP INTO A CONTAINER WHICH CAN BE CLOSED.

Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. AVOID STORAGE NEAR HEAT, STRONG LIGHT (IF CONTAINERS ARE CLEAR), SPARKS OR OPEN FLAMES.

Other Precautions: AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA WITH POOR CIRCULATION.

Exposure Controls

Respiratory Protection: NOT NEEDED

Ventilation: LOCAL EXHAUST IS RECOMMENDED

Protective Gloves: NOT NEEDED

Eye Protection: NOT NEEDED

Supplemental Safety and Health

EFFECTS OF OVEREXPOSURE (CONTD): INGEST: UPSET STOMACH, POSSIBLE IRRITATION.

Chemical Properties

HCC: F4

Boiling Pt: B.P. Text: 320-350F

Vapor Pres: 1.0

Vapor Density: 5.0

Spec Gravity: 0.81

Evaporation Rate & Reference: 0.25, BUTYL ACETATE

Solubility in Water: 0.01 %

Appearance and Odor: BLACK, SLIGHTLY VISCOUS LIQUID, FAINT HYDROCARBON

Percent Volatiles by Volume: 85.0

Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS LIKE CHROMIC ACID LIQUID CHLORINE & CONC O₂

Hazardous Decomposition Products: INCOMPLETELY BURNED C, VARIOUS HYDROCARBONS

Disposal

Waste Disposal Methods: LARGE CONTAINERS OF WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL, FOR EXAMPLE, CONTROLLED BURNING.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.