



## **ELECTRIC DISPERSAN VERSATEC**

### **MSDS Number**

BBCSN

### **National Stock Number**

6850-00D000460

### **Product Name**

ELECTRIC DISPERSAN VERSATEC

### **Manufacturer**

SYNFAX MANUFACTURING INC

### **Product Identification**

Product ID:ELECTRIC DISPERSAN VERSATEC

MSDS Date:01/01/1985

FSC:6850

NIIN:00D000460

MSDS Number: BBCSN

### **Responsible Party**

SYNFAX MANUFACTURING,INC.

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: DO988

### **Contractor**

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

### **Ingredients**

MIXED ISODECANES.

Fraction By Weight: 100%

ACGIH TLV: 300 PPM

### **Hazards**

Effects of Overexposure:HEADACHE,NAUSEA;FOR MORE SEVERE EXPOSURES:MILD DEPRESSION AND OR RESPIRATORY IRR;INGEST:NAUSEA,IRRIT

### **First Aid**

First Aid:INHAL:REMOVE FROM SOLVENT LADEN AREA TO FRESH AIR  
AREA.ACCIDENT INGEST:DO NOT INDUCE VOMITING,CALL DR  
IMMEDIATELY.EYES:FLUSH THOROUGHLY W/CLEAN WARM WATER FOR 15 MINS.IF  
IRRITATION PERSISTS CALL DR.

### **Fire Fighting**

Flash Point:102-107F TCC

Lower Limits:0.8

Upper Limits:7.0

Extinguishing Media:FOAM TYPE EXTINGUISHERS-SUPERIOS TO CO\*2  
EXTINGUISHERS



Fire Fighting Procedures: AVOID WATER-IT TENDS TO SPREAD HYDROCARBON SOLVENT FIRES.

Unusual Fire/Explosion Hazard: NONE

## Accidental Release

Spill Release Procedures: IF AMOUNT IS SMALL (UNDER 1 PINT) ALLOW TO EVAPORATE-INCREASING AIR CIRCULATION IF POSSIBLE, & AVOID ANY SPARKS OR OPEN FLAMES. IF AMOUNT IS LARGE, TRY TO OBTAIN/(CONTAIN) & SOP UP INTO CONTAINER WHICH CAN BE CLOSED.

## Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED. AVOID STORAGE NEAR HEAT, STRONG LIGHT (IF CONTAINERS ARE CLEAR), SPARK OR OPEN FLAMES.

Other Precautions: AVOID USE IN A SMALL CLOSED ROOM OR CONFINED AREA WITH POOR CIRCULATION.

## Exposure Controls

Respiratory Protection: NONE NEEDED

Ventilation: LOCAL EXHAUST IS RECOMMENDED

Protective Gloves: NONE

Eye Protection: NONE

Other Protective Equipment: NONE NEEDED

Supplemental Safety and Health

## Chemical Properties

HCC: F4

Boiling Pt: B.P. Text: 320-350F

Vapor Pres: 2.0

Vapor Density: 5.0

Spec Gravity: 0.784

Evaporation Rate & Reference: 0.45, BUTYL ACETATE

Solubility in Water: 0.01 %

Appearance and Odor: CLEAR, MOBILE, COLORLESS LIQUID, FAINT, HYDROCARBON

Percent Volatiles by Volume: 100

## Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS LIKE CHRONIC ACID, LIQUID CHLORINE & CONC O<sub>2</sub>

## Disposal

Waste Disposal Methods: LARGE CONTAINERS OR WASTE MUST BE HANDLED BY PERSONS OR FIRMS WITH FACILITIES FOR DISPOSAL; FOR EXAMPLE CONTROLLED BURNING.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.