

## **PERMABATCH DEVELOPER**

### **MSDS Number**

BBCZL

### **National Stock Number**

6750-00D000613

### **Product Name**

PERMABATCH DEVELOPER

### **Manufacturer**

SOLUTEK CORP

### **Product Identification**

Product ID: PERMABATCH DEVELOPER

MSDS Date: 01/01/1985

FSC: 6750

NIIN: 00D000613

MSDS Number: BBCZL

### **Responsible Party**

SOLUTEK CORPORATION

94 SHIRLEY ST

BOSTON , MA 02119-3036

US

Cage: EO008

### **Contractor**

SOLUTEK CORPORATION

BOSTON, MA 02119-3036

US

Cage: EO008

### **Ingredients**

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight:

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

SODIUM SULFITE

RTECS: VZ2010000

Fraction By Weight:

HYDROQUINONE (SARA III)

CAS: 123-31-9

RTECS: MX3500000

Fraction By Weight:

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: >75%.

## Hazards

Effects of Overexposure: CAN CAUSE SKIN IRRITATION, & BURNS TO SKIN & EYES, INHALED, MAY BE HARMFUL.

## First Aid

First Aid: MOVE VICTIM TO FRESH AIR; CALL EMERGENCY MEDICAL CARE. REMOVE & ISOLATE CONTAMINATED CLOTHING & SHOES. IN CASE OF CONTACT WITH MATERIAL, IMMEDIATELY FLUSH SKIN OR EYES W/ RUNNING WATER FOR AT LEAST 15 MINS. KEEP VICTIM QUIET & MAINTAIN NORM. BODY TEMP.

## Fire Fighting

Fire Fighting Procedures: WEAR SELF-CONTAINED BREATHING APPARATUS, COOL CONTS W/ WATER.

Unusual Fire/Explosion Hazard: FIRE MAY PRODUCE IRRITATING OR POISONOUS GASES, MAY IGNITE COMBUSTIBLES.

## Accidental Release

Spill Release Procedures: DO NOT TOUCH SPILLED MATERIAL. STOP LEAK IF YOU CAN DO IT WITHOUT RISK. SMALL SPILLS: TAKE UP WITH SAND, OR OTHER NONCOMBUSTIBLE ABSORBENT MATERIAL THEN FLUSH AREA W/ WATER. LARGE SPILLS: DIKE FAR AHEAD OF SPILL FOR LATER DISPOSAL.

## Handling

Handling and Storage Precautions: STORE IN DRY PLACE TO PREVENT CORROSION OF THE SURFACE OF THE DRUM, ABSORPTION OF MOISTURE, FREEZING, ETC; FOR OUTDOORS, PROTECT W/ SOME INSULATION/HTG SYST

Other Precautions: WEAR RUBBER/PLASTIC GLOVES, BIG FACE SHIELD & WORKING CLOTHES.

## Exposure Controls

Respiratory Protection: WEAR SELF-CONTAINED BREATHING APPARATUS.

Ventilation: LOCAL EXHAUST IS PREFERRED TO REMOVE FUMES.

Protective Gloves: RUBBER/PLASTIC

Eye Protection: SAFETY GLASSES.

Other Protective Equipment: WEAR FULL PROTECTIVE CLOTHING, RUBBER OR PLASTIC APRON.

Supplemental Safety and Health

## Chemical Properties

HCC: B3

Boiling Pt: B.P. Text: >212F

Spec Gravity: 1.094

Solubility in Water: COMPLETE

Appearance and Odor: YELLOW AQUEOUS SOLUTION. NO ODOR

## Stability

Stability Indicator/Materials to Avoid: YES

WOOD, PAPER, OIL, ETC.

## Disposal

Waste Disposal Methods:PUT INTO LARGE VESSEL CONTAINING WATER.DISCHARGE INTO AN APPROVED DISPOSAL AREA W/SUFFICIENT WATER ALL IAW FEDERAL,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.