

RUBBER SOLVENT-COLEMAN FUEL

MSDS Number

BBCZM

National Stock Number

6850-00D000614

Product Name

RUBBER SOLVENT-COLEMAN FUEL

Manufacturer

UNION OIL COMPANY OF CALIFORNIA UNION CHEMICAL DIV

Product Identification

Product ID: RUBBER SOLVENT-COLEMAN FUEL

MSDS Date: 01/01/1985

FSC: 6850

NIIN: 00D000614

MSDS Number: BBCZM

Responsible Party

UNION OIL COMPANY OF CALIFORNIA, UNION CHEMICAL DIV

1345 N. MEACHAM

SCHAUMBURG, IL 60196

US

Emergency Phone: 800-356-3129 (POISON CONTROL CNTR)

Info Phone: 312-619-2644

Cage: 5W523

Contractor

UNOCAL CHEMICALS DIV., UNION OIL OF CALIFORNIA

SCHAUMBURG, IL 60196

US

312-490-2500/800-424-9300 (CHEMTREC)

Cage: 94684

Ingredients

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: VL8047000

Fraction By Weight: 100%.

OSHA PEL 100 PPM

Hazards

Effects of Overexposure: DRYING OF SKIN, EYE IRRITATION. EXCESSIVE INHALATION MAY CAUSE ANESTHESIA, HEADACHE, DIZZY, NAUSEA, R. IRR.

First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR, APPLY ARTIFICIAL RESPIRATION IF NECESSARY, CALL A DOCTOR. SKIN CONTACT: WASH WITH MILD SOAP & WATER, APPLY MILD SKIN CREAM. EYE CONTACT: FLUSH WITH WATER, CALL A DOCTOR. INGESTION: CALL A DOCTOR.

Fire Fighting

Flash Point:25F TCC
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL,WATER SPRAY
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS;H*2O
AS COOLANT.

Accidental Release

Spill Release Procedures:FLUSH W/WATER INTO RETAINING AREA OR
CONTAINER.AVOID SPARKS FIRE OR HOT METAL SURFACES. SMALL QUANTITIES
MAY BE ABSORBED ONTO AN APPROPRIATE ABSORBENT.

Handling

Handling and Storage Precautions:KEEP COOL & AWAY FROM SOURCES OF
IGNITION.USE WITH ADEQUATE VENTILATION.AVOID REPEATED PERSONAL
CONTACT.

Exposure Controls

Respiratory Protection:CARTRIDGE RESPIRATOR OR GAS MASK.
Ventilation:LOCAL EXHAUST TO KEEP WORKROOM CONCENTRATION BELOW TLV.
Protective Gloves:IMPERMEABLE
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:APRON,BARRIER CREAM.
Supplemental Safety and Health

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:105-120F
Vapor Pres:155
Vapor Density:3.5
Spec Gravity:0.70
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIQUID

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT,SPARKS,OPEN FLAME,FIRE.
Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CO &
CO*2.

Disposal

Waste Disposal Methods:INCINERATE UNDER SAFE CONDITIONS OR DISPOSE OF
IAW APPLICABLE LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.