## 404-0080, REPROFIX L FIXER, PART A

#### **MSDS Number**

**BBDBB** 

#### **National Stock Number**

6750-00D000631

#### **Product Name**

404-0080, REPROFIX L FIXER, PART A

#### Manufacturer

ANITEC IMAGE CORP

### **Product Identification**

Product ID:404-0080, REPROFIX L FIXER, PART A MSDS Date: 01/01/1985 FSC:6750 NIIN:00D000631 MSDS Number: BBDBB

**Responsible Party** 

#### ANITEC IMAGE CORPORATION

40 CHARLES ST

BINGHAMPTON, NY 13902

US

Emergency Phone: (607) 774-3300

Info Phone: 607-774-3300

Cage: 61263

# **Contractor**

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333 Cage: 61263

# **Ingredients**

WATER; CAS #7732-18-5; (% WT BY DIFFERENCE)

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 97.6%

ACETIC ACID (SARA III)

CAS: 64-19-7 RTECS: AF1225000

Fraction By Weight: 2.35%

OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192 EPA Report Quantity: 5000 LBS



DOT Report Quantity: 5000 LBS

#### **Hazards**

Effects of Overexposure: MAY CAUSE SKIN/EYE IRRITATION ON CONTACT

#### First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*20.IF IRRITATION OCCURS,GET MED HELP;INGESTION:

### **Fire Fighting**

Flash Point: NONE

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG APP H\*20 SPRAY TO COOL

CONTR.

Unusual Fire/Explosion Hazard: KNOWN

#### **Accidental Release**

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. STOP LEAK. H\*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS. LG SPILL: DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

#### Handling

Handling and Storage Precautions: STORE IN COOL DRY WELL VENTILATED AREA; KEEP CONTAINER TIGHTLY CLOSED; WASH THOROUGHLY AFTER HANDLING. Other Precautions: NONE KNOWN

### **Exposure Controls**

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: PROVIDE MECHAN(GEN/LOCAL EXHAUST) VENT TO MAINTN Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT

CONTACT.

Supplemental Safety and Health

OLD CAT #5200-018;UNIT CONTNR QTY:50 GAL TO MAKE 200 GAL;MFR SPECIFIED 1/12/84,BOTH PARTS A & B REQUIRED TO MAKE 200 GAL WORKING SOLN;IF

ANY QUESTION ARISES, CALL 1-800-847-9368/1062(2 PT KIT)

#### **Chemical Properties**

HCC:N1

Boiling Pt:B.P. Text:200F

Spec Gravity:1.33

Solubility in Water: COMPLETE

Appearance and Odor: COLORLESS LIQUID, ODOR OF VINEGER

#### Stability

Stability Indicator/Materials to Avoid:YES PER MFR,NO SPECIFIC INCOMPATIBILITY Stability Condition to Avoid:NONE KNOWN

#### **Disposal**

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.



https://msdsreport.com/msds/BBDBB

•