

401-0047,REPROTYPE DEVELOPR/REPLNSHR,PART B

MSDS Number

BBDBM

National Stock Number

6750-00D000639

Product Name

401-0047,REPROTYPE DEVELOPR/REPLNSHR,PART B

Manufacturer

ANITEC IMAGE CORP

Product Identification

Product ID:401-0047,REPROTYPE DEVELOPR/REPLNSHR,PART B

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000639

MSDS Number: BBDBM

Responsible Party

ANITEC IMAGE CORPORATION

40 CHARLES ST

BINGHAMTON , NY 13902

US

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

Ingredients

ACETIC ACID (SARA III)

CAS: 64-19-7

RTECS: AF1225000

Fraction By Weight: 37.0%

OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PHENIDONE;CAS #92-43-3

CAS: 92-43-3

RTECS: UQ8750000

Fraction By Weight: 3.20%

WATER;CAS #7732-18-5;(WT BY DIFFERENCE)

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 59.8%

Hazards

Effects of Overexposure:MAY CAUSE EYE BURNS AND SKIN IRRITATION.

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H*2O.WASH W/SOAP & WATER.REMOVE CONTAMINATED CLOTHING.GET MED ATTN FOR IRRITATION;ING:DO NOT INDUCE VOMIT ING.GIVE MAGNESIA OR CHALK IN WATER.GETMED HELP.

Fire Fighting

Flash Point:NONE

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:USE H*20 TO COOL EXPD CONTRS. USE SCBA & FULL PROT.CLTHG.

Unusual Fire/Explosion Hazard:MAY EMIT TOXIC FUMES.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;AVOID TEMPERATURE EXTREMES.

Other Precautions:DO NOT GET LIQUID ON SKIN,CLOTHING,OR IN EYES.WASH AFTER HANDLING.

Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.

Supplemental Safety and Health

PART B OF TWO PART PRODUCT;BOTH PARTS REQD TO MAKE WORKING SOLUTION;UNIT CONTNR QTY OF PART B IS 5 GAL BOTTLE;SEE NSN 6750-00-D00-0638 FOR PART A DATA;OLD CAT # 5201-702 OF PART B.KEY1:C1.

Chemical Properties

HCC:C2

Boiling Pt:B.P. Text:220F

Spec Gravity:1.088

Solubility in Water:COMPLETE

Appearance and Odor:CONCENTRATE BROWNISH COLOR,PUNGENT VINEGAR ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

FLAMMABLES, OXIDIZERS

Stability Condition to Avoid:NONE KNOWN

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.