

5202-602,REPROLITH LITHGRAPHIC DEVLPR,PART A

MSDS Number

BBDBN

National Stock Number

6750-00D000641

Product Name

5202-602,REPROLITH LITHGRAPHIC DEVLPR,PART A

Manufacturer

ANITEC IMAGE CORP

Product Identification

Product ID:5202-602,REPROLITH LITHGRAPHIC DEVLPR,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000641

MSDS Number: BBDBN

Responsible Party

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

Ingredients

HYDROQUINONE (SARA III)

CAS: 123-31-9

RTECS: MX3500000

Fraction By Weight: 8.0%

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

SODIUM-POTASSIUM FORMALDEHYDE BISULFITE

Fraction By Weight: 30.0%

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight: 0.5%

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

WATER;CAS #7732-18-5 ;% WT BY DIFFERENCE

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 61.5%

Hazards

Effects of Overexposure:MAY CAUSE IRRITATION TO SKIN OR EYES.

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED
ATTN;SKIN:FLUSH/WASH W/PLENTY OF H*2O.IF IRRITATION OCCURS,GET MED
HELP

Fire Fighting

Flash Point:NONE

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H*20 SPRAY TO COOL
CONTR.

Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. STOP LEAK. H*2O
SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE
VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS.
LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED
AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING.
Other Precautions:PH OF SOLUTION OF PART A=6.665

Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY
CONDITIONS/ADEQUATE VENT.

Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT
CONTACT.

Supplemental Safety and Health

PART A OF 2 PART PROD;MFR STATED 1/13/84,ABOVE CAT # WAS USED BY GAF
CORP;ITEM TRNSFRD TO ANITEC WHO IS NOW USING CAT #5202-609;ITEM IS
NOT ANY MORE MANUFACTURD;SEE ADDL DATA FOR PART B INFO.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:210F

Spec Gravity:1.301

Solubility in Water:COMPLETE

Appearance and Odor:CONCENTRATE,CLEAR,COLORLESS LIQ,PUNGENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

NO SPECIFIC INCOMPATIBILITY.

Stability Condition to Avoid:NONE KNOWN

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.