

# 5202-702, REPROLITH LITHGRAPHC DEVLPR, PART B

## **MSDS Number**

**BBDBP** 

## **National Stock Number**

6750-00D000642

### **Product Name**

5202-702, REPROLITH LITHGRAPHC DEVLPR, PART B

#### Manufacturer

ANITEC IMAGE CORP

## **Product Identification**

Product ID:5202-702,REPROLITH LITHGRAPHC DEVLPR,PART B

MSDS Date:01/01/1985

FSC:6750 NIIN:00D000642

MSDS Number: BBDBP

## **Responsible Party**

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

### Contractor

ANITEC IMAGE CORP

4444

US

BINGHAMTON, NY 13902

607-774-3333

Cage: 61263

## **Ingredients**

POTASSIUM BROMIDE; CAS #7758-02-3

CAS: 7758-02-3

RTECS: TS7650000

Fraction By Weight: 1.10%

SODIUM SULFITE; CAS #7757-83-7

CAS: 7757-83-7

RTECS: WE2150000

Fraction By Weight: 1.20%

POTASSIUM CARBONATE; CAS #584-08-7

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 31.0%



WATER; CAS #7732-18-5; % WT BY DIFFERENCE

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 66.7%

Hazards

Effects of Overexposure: MAY CAUSE SKIN OR EYES IRRITATION.

#### First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*20.IF IRRITATION OCCURS,GET MED HELP

## **Fire Fighting**

Flash Point: NONE

Extinguishing Media: CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG APP H\*20 SPRAY TO COOL

CONTR.

Unusual Fire/Explosion Hazard: UNKNWON

#### **Accidental Release**

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS: LG SPILL: DI KE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:PH OF PART B SOLUTION:11.25

## **Exposure Controls**

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: MECHANICAL (GENERAL) RECOMMENDED, LOCAL EXHAUST IF NEEDED

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT

CONTACT.

Supplemental Safety and Health

PART B OF PROD; MFR STATED 1/13/84, ABOVE CAT # WAS USED BY GAF CORP; ITEM TRNSFRRD TO ANITEC WHO IS NOW USING CAT # 5202-709; ITEM IS NOT ANY MORE MANUFACTURD; SEE ADDL DATA FOR PART A INFO. KEY1:N1.

## **Chemical Properties**

Boiling Pt:B.P. Text:210F Spec Gravity:1.338

Solubility in Water: COMPLETE

Appearance and Odor: CONCENTRATE, COLORLESS, CLEAR LIQD, MILD ODOR.

# Stability

Stability Indicator/Materials to Avoid:YES
PER MFR,NO SPECIFIC INCOMPATIBILITY;BUT AVOID OXIDZR/FLAMM
Stability Condition to Avoid:NONE KNOWN

#### Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,



expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.