

# 5202-002, REPROLITH LITHGRAPHC DEVLPR, PART B

#### **MSDS Number**

BBDBQ

#### **National Stock Number**

6750-00D000643

#### **Product Name**

5202-002, REPROLITH LITHGRAPHC DEVLPR, PART B

#### Manufacturer

ANITEC IMAGE CORP

## **Product Identification**

Product ID:5202-002,REPROLITH LITHGRAPHC DEVLPR,PART B MSDS Date:01/01/1985 FSC:6750 NIIN:00D000643 MSDS Number: BBDBQ

## **Responsible Party**

#### ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

#### Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

## Ingredients

POTASSIUM BROMIDE; CAS #7758-02-3

CAS: 7758-02-3

RTECS: TS7650000

Fraction By Weight: 1.10%

SODIUM SULFITE;CAS #7757-83-7 CAS: 7757-83-7 RTECS: WE2150000 Fraction By Weight: 1.20%

POTASSIUM CARBONATE; CAS #584-08-7 CAS: 584-08-7 RTECS: TS7750000 Fraction By Weight: 31.0%



https://msdsreport.com/msds/BBDBQ

WATER;CAS #7732-18-5; % WT BY DIFFERENCE

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 66.7%

## Hazards

Effects of Overexposure: MAY CAUSE SKIN OR EYES IRRITATION.

## **First Aid**

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*20.IF IRRITATION OCCURS,GET MED HELP

•

# **Fire Fighting**

Flash Point:NONE Extinguishing Media:CO\*2, FOAM, DRY CHEM. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG APP H\*20 SPRAY TO COOL CONTR.

## **Accidental Release**

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS:LG SPILL:DI KE W COMMERCIAL ABSORBENT,PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:PH OF SOLUTION IS 11.25

# **Exposure Controls**

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT. Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED Protective Gloves:IMPERVIOUS Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT. Supplemental Safety and Health PART B OF 2 PART PROD;MFR STATED 1/13/84,ABOVE CAT # WAS USED BY GAF CORP;ITEM TRNSFRRD TO ANITEC WHO IS NOW USING CAT # 5202-609;ITEM IS NOT ANY MORE MANUFACTURD:SEE ADDL DATA FOR PART A INFO.KEY1:N1 .

## **Chemical Properties**

HCC:N1 Boiling Pt:B.P. Text:210F Spec Gravity:1.338 Solubility in Water:COMPLETE Appearance and Odor:CONCENTRATE,COLORLESS,CLEAR LIQD,MILD ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES PER MFR,NO SPECIFIC INCOMPATIBILITY;BUT AVOID OXIDZR/FLAMM Stability Condition to Avoid:NONE KNOWN

## Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,



https://msdsreport.com/msds/BBDBQ

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.