

400-0090,REPLITH LITHGRAPHIC DEVLPR,PART A

MSDS Number

BBDBW

National Stock Number

6750-00D000648

Product Name

400-0090,REPLITH LITHGRAPHIC DEVLPR,PART A

Manufacturer

ANITEC IMAGE CORP

Product Identification

Product ID:400-0090,REPLITH LITHGRAPHIC DEVLPR,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000648

MSDS Number: BBDBW

Responsible Party

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

Ingredients

SODIUM FOR MALDEHYDE BISULFITE

Fraction By Weight: 27.5%

HYDROQUINONE (SARA III)

CAS: 123-31-9

RTECS: MX3500000

Fraction By Weight: 9.2%

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED;% WT BY

Fraction By Weight: 63.3%

Hazards

Effects of Overexposure:MAY CAUSE IRRITATION TO SKIN OR EYES.

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H*2O. IF IRRITATION OCCURS,GET MED HELP.

Fire Fighting

Flash Point:NONE

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:NONE

Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:MECHANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GOGGLE W/SIDESHLD.

Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.

Supplemental Safety and Health

PART A OF 2 PART PRODUCT;OLD P/N 5202-015 WHICH WAS USED BY FGAF CORP BEFORE ITEM TRANSFER TO ANITEC CORP;SEE P/N IND "B" FOR PART B DATA UNDER THIS NSN;PH AT 25C=6.8;MSDS FM MFR UNDATED.KEY1:N1.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:210F

Spec Gravity:1.232

Solubility in Water:COMPLETE

Appearance and Odor:CONCENTRATE LIQUID,PUNGENT ODOR.

Stability

Stability Indicator/Materials to Avoid:YES

NO SPECIFIC INCOMPATIBILITY,PER MFR.

Stability Condition to Avoid:NONE KNOWN

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.