

# 400-0003, REPRLITH LITHGRAPHC DEVLPR, PART A

## **MSDS Number**

**BBDBY** 

#### **National Stock Number**

6750-00D000649

### **Product Name**

400-0003, REPRLITH LITHGRAPHC DEVLPR, PART A

#### Manufacturer

ANITEC IMAGE CORP

### **Product Identification**

Product ID:400-0003,REPRLITH LITHGRAPHC DEVLPR,PART A MSDS Date:01/01/1985 FSC:6750

NIIN:00D000649 MSDS Number: BBDBY

## **Responsible Party**

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

US

BINGHAMTON, NY 13902

607-774-3333 Cage: 61263

## **Ingredients**

SODIUM FORMALDEHYDE BISULFITE

Fraction By Weight: 27.5%

HYDROQUINONE (SARA III)

CAS: 123-31-9 RTECS: MX3500000

Fraction By Weight: 9.2%

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192 EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED; % WT BY

Fraction By Weight: 63.3%

**Hazards** 



Effects of Overexposure: MAY CAUSE IRRITATION TO SKIN OR EYES.

#### First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*20.IF IRRITATION OCCURS,GET MED HELP;

## **Fire Fighting**

Flash Point: NONE

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG APP H\*20 SPRAY TO COOL

CONTR.

### **Accidental Release**

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. STOP LEAK. H\*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS. LG SPILL: DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:NONE

## **Exposure Controls**

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: MECHANICAL (GENERAL) RECOMMENDED, LOCAL EXHAUST IF NEEDED

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT

CONTACT.

Supplemental Safety and Health

PART A OF 2 PART PRODUCT:OLD P/N 5202-609 WHICH WAS USED BY GAF CORP BEFORE ITEM TRANSFER TO ANITEC CORP:SEE P/N IND "A" FOR PART B DATA

UNDER 6750-00-D00

## **Chemical Properties**

Boiling Pt:B.P. Text:210F

Spec Gravity:1.232

Solubility in Water: COMPLETE

Appearance and Odor: CONCENTRATE LIQUID, PUNGENT ODOR.

#### Stability

Stability Indicator/Materials to Avoid:YES NO SPECIFIC INCOMPATIBILITY.

Stability Condition to Avoid: NONE KNOWN

## **Disposal**

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.