

400-0006, REPRLITH LITHGRAPHC DEVLPR, PART B

MSDS Number

BBDBZ

National Stock Number

6750-00D000650

Product Name

400-0006, REPRLITH LITHGRAPHC DEVLPR, PART B

Manufacturer

ANITEC IMAGE CORP

Product Identification

Product ID:400-0006, REPRLITH LITHGRAPHC DEVLPR, PART B

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000650 MSDS Number: BBDBZ

Responsible Party

ANITEC IMAGE CORPORATION

Emergency Phone: (607)774-3300

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

US

BINGHAMTON, NY 13902

607-774-3333

Cage: 61263

Ingredients

POTASSIUM CARBONATE; CAS #584-08-7

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 20.7%

SODIUM SULFITE; CAS #7757-83-7

CAS: 7757-83-7

RTECS: WE2150000

Fraction By Weight: 2.7%

SODIUM BROMIDE; CAS #7647-15-6

CAS: 7647-15-6 RTECS: VZ3150000

Fraction By Weight: 1.0%



POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3 RTECS: TT2100000

Fraction By Weight: 0.5% OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

WATER; CAS #7732-18-5; % WT BY DIFFERENCE

CAS: 7732-18-5 RTECS: ZC0110000

Fraction By Weight: 75.1%

Hazards

Effects of Overexposure: MAY CAUSE IRRITATION TO SKIN OR EYES

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OGF H*20.IF IRRITATION OCCURS,GET MED HELP;

Fire Fighting

Flash Point:NONE

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG APP H*20 SPRAY TO COOL

CONTR.

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. STOP LEAK. H*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS. LG SPILL: DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:NONE

Exposure Controls

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY

CONDITIONS/ADEQUATE VENT.

Ventilation: MECHANICAL (GENERAL) RECOMMENDED, LOCAL EXHAUST IF NEEDED

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT

CONTACT.

Supplemental Safety and Health

PART B OF 2 PART PRODUCT; OLD P/N 5202-709 WHICH WAS USED BY GAF CORP BEFORE ITEM TRANSFER TO ANITEC CORP; SEE P/N IND "A" FOR PART A DATA

UNDER 6750-00 D00-0649.KEY1:

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:210F Spec Gravity:1.313

Solubility in Water: COMPLETE

Appearance and Odor: CONCENTRATED LIQUID, MILD ODOR.

Stability



Stability Indicator/Materials to Avoid:YES NO SPECIFIC INCOMPATIBILITY.
Stability Condition to Avoid:NONE KNOWN

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.