

## **400-0011,REPLITH LITHGRAPHIC REPL,PART A**

### **MSDS Number**

BBDCB

### **National Stock Number**

6750-00D000651

### **Product Name**

400-0011,REPLITH LITHGRAPHIC REPL,PART A

### **Manufacturer**

ANITEC IMAGE CORP

### **Product Identification**

Product ID:400-0011,REPLITH LITHGRAPHIC REPL,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000651

MSDS Number: BBDCB

### **Responsible Party**

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

### **Contractor**

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

### **Ingredients**

HYDROQUINONE (SARA III)

CAS: 123-31-9

RTECS: MX3500000

Fraction By Weight: 9.9%

OSHA PEL2 MG/M3

ACGIH TLV: 2 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED;% WT BY

Fraction By Weight: 90.1%

### **Hazards**

Effects of Overexposure:MAY BE IRRITATING TO SKIN & EYES ON CONTACT.

### **First Aid**

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED  
ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*2O.IF IRRITATION OCCURS,GET MED

HELP.

## Fire Fighting

Flash Point:NONE

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. STOP LEAK. H\*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS. LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING.

Other Precautions:NONE KNOWN

## Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:IMPERVIOUS

Eye Protection:CHEM SPLASH GOGGLES

Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.

Supplemental Safety and Health

MSDS FM MFR UNDATED:OLD CATALOG NUMBER OF GAF CORP IS 5202-610;THIS IS PART A OF TWO PART PRODUCT;UNIT CONTNR QTY IS 5 GAL;

## Chemical Properties

Boiling Pt:B.P. Text:210F

Spec Gravity:1.186

Solubility in Water:COMPLETE

Appearance and Odor:CONCENTRATED LIQUID,SLIGHT METHANOLIC ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES

PER MFR,NO SPECIFIC INCOMPATIBILITY

Stability Condition to Avoid:NONE KNOWN

## Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.