

# 400-0005, REPROLITH LITHGRAPHC REPL, PART B

#### **MSDS Number**

BBDCC

#### **National Stock Number**

6750-00D000652

## **Product Name**

400-0005, REPROLITH LITHGRAPHC REPL, PART B

#### Manufacturer

ANITEC IMAGE CORP

## **Product Identification**

Product ID:400-0005,REPROLITH LITHGRAPHC REPL,PART B MSDS Date:01/01/1985 FSC:6750 NIIN:00D000652 MSDS Number: BBDCC

## **Responsible Party**

#### ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

#### Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

## Ingredients

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight: 1.2%

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

SODIUM SULFITE;CAS #7758-83-7 CAS: 7757-83-7 RTECS: WE2150000 Fraction By Weight: 4.8%



https://msdsreport.com/msds/BBDCC

•

POTASSIUM CARBONATE;CAS #584-08-7

CAS: 584-08-7

RTECS: TS7750000

Fraction By Weight: 15.9%

SODIUM BROMIDE;CAS #7647-15-6

CAS: 7647-15-6

RTECS: VZ3150000

Fraction By Weight: 0.3%

#### Hazards

Effects of Overexposure: MODERATELY ALKALINE, IRRITATING TO SKIN AND EYES.

## **First Aid**

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/WASH W/PLENTY OF H\*20.IF IRRITATION OCCURS,GET MED HELP

## **Fire Fighting**

Flash Point:NONE Extinguishing Media:CO\*2, FOAM, DRY CHEM. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR. Unusual Fire/Explosion Hazard:NONE

## Accidental Release

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. STOP LEAK. H\*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT,SHOVEL INTO METAL DRUMS. LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING. Other Precautions:NONE KNOWN.

## **Exposure Controls**

Respiratory Protection:NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT. Ventilation:MECHANICAL(GENERAL):SATISFACTORY Protective Gloves:IMPERVIOUS Eye Protection:CHEM SPLASH GOGGLES Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT. Supplemental Safety and Health THIS DATA DESCRIBES PART B OF TWO PART PRODUCT;THE OLD CAS # OF GAF CORP(BEFORE TRANSFER TO ANITEC) IS 5202-710:SEE 675000D000651 FOR PART A;MSDS UNDATED:BOTH PARTS REQD TO MAKE 30 GAL SOLN.KEY1:

## **Chemical Properties**

HCC:N1 Boiling Pt:B.P. Text:210F Spec Gravity:1.252 Solubility in Water:COMPLETE Appearance and Odor:CONCENTRATED LIQUID,SLIGHT ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES



PER MFR,NO SPECIFIC INCOMPATIBILITY Stability Condition to Avoid:NONE KNOWN

#### Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.