

## **402-0055,REPROMATIC LIQUID FIXER**

### **MSDS Number**

BBDCG

### **National Stock Number**

6750-00D000656

### **Product Name**

402-0055,REPROMATIC LIQUID FIXER

### **Manufacturer**

ANITEC IMAGE CORP

### **Product Identification**

Product ID:402-0055,REPROMATIC LIQUID FIXER

MSDS Date:01/01/1985

FSC:6750

NIIN:00D000656

MSDS Number: BBDCG

### **Responsible Party**

ANITEC IMAGE CORPORATION

Emergency Phone: (607)774-3300

Cage: 61263

### **Contractor**

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333

Cage: 61263

### **Ingredients**

AMMONIUM THIOSULFATE;CAS #7783-18-8;% WT=16.5% OF

CAS: 7783-18-8

RTECS: XN6465000

Fraction By Weight: 9.90%

ACETIC ACID (SARA III)

CAS: 64-19-7

RTECS: AF1225000

Fraction By Weight: 0.95%

OSHA PEL10 PPM

ACGIH TLV: 10 PPM/15 STEL; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

SODIUM METABISULFITE

CAS: 7681-57-4

RTECS: UX8225000

Fraction By Weight: 190%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

AMMONIUM THIOCYANATE (SARA III)

CAS: 1762-95-4

RTECS: XK7875000

Fraction By Weight: 4.28%

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED;% WT BY

Fraction By Weight: 83.0%

## Hazards

Effects of Overexposure:MAY CAUSE IRRITATION TO SKIN & EYES.

## First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN;SKIN:FLUSH/ W/PLENTY OF H\*20.WASH W/SOAP & WATER.GET MED ATTN IF IRRITATION OCCURS.

## Fire Fighting

Flash Point:NONE

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR.

## Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK. EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG SPILL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

## Handling

Handling and Storage Precautions:STORE IN COOL DRY WELL VENTILATED AREA;KEEP CONTAINER TIGHTLY CLOSED;WASH THOROUGHLY AFTER HANDLING;NORMAL WAREHOUSING SATISFACTORY.  
Other Precautions:NONE.

## Exposure Controls

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.  
Ventilation:MECHANICAL(GENERAL):SATISFACTORY  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY/CHEM GOGGLES  
Other Protective Equipment:WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.  
Supplemental Safety and Health  
OLD CAT #5203-007 USED BY GAF CORP BEFORE TRNSFR TO ANITEC CORP;MSDS NOT DATED.

## Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F

Spec Gravity:1.121

Solubility in Water:COMPLETE

Appearance and Odor:CONCENTRATED LIQUID,MILD ODOR.

## Stability

Stability Indicator/Materials to Avoid:YES  
PER MFR NO SPECIFIC INCOMPATIBILITY  
Stability Condition to Avoid:NONE KNOWN

## Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.