403-0074, REPROCOPY GC-71 ACTIVATOR

MSDS Number

BBDCM

National Stock Number

6750-00D000660

Product Name

403-0074, REPROCOPY GC-71 ACTIVATOR

Manufacturer

ANITEC IMAGE CORP

Product Identification

Product ID:403-0074,REPROCOPY GC-71 ACTIVATOR MSDS Date:01/01/1985 FSC:6750 NIIN:00D000660

NIIN:00D000660 MSDS Number: BBDCM

Responsible Party

ANITEC IMAGE CORPORATION

Emergency Phone: (607) 774-3300

Cage: 61263

Contractor

ANITEC IMAGE CORP

4444

BINGHAMTON, NY 13902

US

607-774-3333 Cage: 61263

Ingredients

SODIUM HYDROXIDE (SARA III)

CAS: 1310-73-2

RTECS: WB4900000 Fraction By Weight: 0.2%

OSHA PEL2 MG/M3

ACGIH TLV: C 2 MG/M3; 9293 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

SODIUM BROMIDE; CAS #7647-15-6

CAS: 7647-15-6 RTECS: VZ3150000

Fraction By Weight: 0.1%

2-DIETHYLAMINOETHANOL

CAS: 100-37-8



RTECS: KK5075000

Fraction By Weight: 9.9%

OSHA PELS, 10 PPM

ACGIH TLV: S, 10 PPM; 9192

AQUEOUS SOLUTION, HAZARD UNKNOWN, UNIDENTIFIED; % WT BY

Fraction By Weight: 89.8%

Hazards

Effects of Overexposure: MAY CAUSE SKIN IRRITATION AND EYE BURNS.

First Aid

First Aid: EYES: FLUSH WITH PLENTY OF WATER AT LEAST FOR 15 MIN & GET MED ATTN; SKIN: FLUSH/WASH W/PLENTY OF H*20. IF IRRITATION OCCURS, GET MED HELP.

Fire Fighting

Flash Point: NONE Extinguishing Media:CO*2, FOAM, DRY CHEM. Fire Fighting Procedures: WEAR SELF-CNTD BRTHG, APP H*20 SPRAY TO COOL CONTR

Accidental Release

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. STOP LEAK. H*20 SPRAY TO COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS. LG SPILL:DIKE W COMMERCIAL ABS ORBENT, PUMP INTO COVERED DRUMS.

Handling

Handling and Storage Precautions: STORE IN COOL DRY WELL VENTILATED AREA; KEEP CONTAINER TIGHTLY CLOSED; WASH THOROUGHLY AFTER HANDLING; NORMAL WAREHOUSE SATISFACTORY Other Precautions: NONE KNOWN.

Exposure Controls

Respiratory Protection: NO SPECIAL REQMNTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:LOCAL EXHAUST PREFERRED, MECHANICAL EXHAUST ACEPTABLE.

Protective Gloves: IMPERVIOUS

Eye Protection: SAFETY/CHEM GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS APRON/CLOTHING TO PREVENT CONTACT.

Supplemental Safety and Health

MSDS FM MFR UNDATED; THE OLD CAT #5204-004 USED BY GAF CORP BEFORE TRNSFR TO ANITEC, INC, PH OF PRODUCT AT 25C=12.52.

HCC:N1

Boiling Pt:B.P. Text:200F

Chemical Properties

Spec Gravity: 1.063

Solubility in Water: COMPLETE

Appearance and Odor: ALKALINE SOLUTION; AMINE ODOR

Stability

Stability Indicator/Materials to Avoid:YES MFR NOTES:NO SPECIFIC INCOMPATIBILITY. Stability Condition to Avoid: NONE KNOWN

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.