



ROYCO 601

MSDS Number

BBDDC

National Stock Number

9150-00D000680

Product Name

ROYCO 601

Manufacturer

ROYAL LUBRICANTS COMPANY INC

Product Identification

Product ID:ROYCO 601
MSDS Date:01/01/1985
FSC:9150
NIIN:00D000680
MSDS Number: BBDDC

Responsible Party

ROYAL LUBRICANTS COMPANY,INC
Emergency Phone: (201) 887-3100
Cage: 07950

Contractor

ROYAL LUBRICANTS COMPANY INC.
518
EAST HANOVER, NJ 07936
US
973-887-7411/7410
Cage: 07950

Ingredients

SILICONE- DIESTER BLEND
Fraction By Weight: 100%

First Aid

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Flash Point:440F-COC
Upper Limits:UNK
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:DO NOT USE WATER JETS.USE AIR SUPPLIED BREATHING EQUIPMENT.
Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:ELIM IGNITION SOURCES.EVACUATE UNPROTECTED PERSONS.STOP LEAK W/O RISK;SMALL SPILL:ABSORB W/CLAY DIATOMACEOUS EARTH,OTHER INERT MATL & SHOVEL INTO CONTAINERS;LG SPILL:DIKE LIQUID FOR LATER DISPOSAL;SHO ULD NOT CONTAMINATE RIVERS,WATERWAYS/SEWER SYSTEM.



Handling

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED
Other Precautions:WASH HANDS THOROUGHLY W/SOAP & WARM WATER BEFORE HANDLING FOOD OR SMOKE.

Exposure Controls

Respiratory Protection:AIR SUPPLIED BREATHING EQUIPMENT IF OIL MIST IS GENERATED
Ventilation:LOCAL EXHAUST:AS REQUIRED IF MIST IS BEING GENERATED
Protective Gloves:RUBBER
Eye Protection:GOGGLES
Other Protective Equipment:NONE KNOWN
Supplemental Safety and Health
MSDS FM MFR UNDATED;PER MFR MIL SPEC REFERENCE:MIL-L-19701

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:>700F
Vapor Pres:UNK
Vapor Density:UNK
Spec Gravity:0.9135
Solubility in Water:NEGLIGIBLE
Appearance and Odor:LOW-VISCOSITY OIL
Percent Volatiles by Volume:UNK

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS SUCH AS LIQUID OXYGEN
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:FORMS SMOKE,FUMES,CARBON MONOXIDE DURING COMBUSTION/PAST F.P

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.