

## **UNIVOLT N 61**

### **MSDS Number**

BBDFY

### **National Stock Number**

9160-00D000731

### **Product Name**

UNIVOLT N 61

### **Manufacturer**

EXXON CO USA

### **Product Identification**

Product ID:UNIVOLT N 61

MSDS Date:01/01/1987

FSC:9160

NIIN:00D000731

MSDS Number: BBDFY

### **Responsible Party**

EXXON CO, USA.

Emergency Phone: 713-656-3424

Cage: EO029

### **Contractor**

EXXON COMPANY U.S.A.

HOUSTON, TX 77252-2180

US

713-656-5949 / 713-656-3424

Cage: 29700

### **Ingredients**

PETROLEUM HYDROCARBON

### **Hazards**

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION.

### **First Aid**

First Aid:SKIN:WASH W.SOAP & H\*2O. EYES:FLUSH W. H\*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

### **Fire Fighting**

Flash Point:320F/160C(COC)

Lower Limits:1

Upper Limits:7

Extinguishing Media:SM:CO\*2, DRY CHEM. LG:H\*2O SPRAY,FOG OR FOAM

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*2O SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

### **Accidental Release**

Spill Release Procedures:RECOVER FREE LIQ.ADD ABSORBENT TO SPILL AREA.KEEP PETROLEUM PRODUCTS OUT OF SEWER & WATERCOURSES BY DIKING OR IMPOUNDING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY

ENTER SEWERS, WATERCOURSES.

## Handling

Handling and Storage Precautions: KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions: REMOVE OIL-SOAKED CLOTHING & LAUNDRY BEFORE RE-USE.

## Exposure Controls

Respiratory Protection: NORMALLY NONE

Ventilation: LOCAL EXHAUST & > 60 FPM HOOD OR FACE VELOCITY.

Protective Gloves: CHEM-RESISTANT

Eye Protection: CHEM SPLASH GOGGLES

Other Protective Equipment: CHEM-RESIST APRON OR CLOTHING.

Supplemental Safety and Health

MSDS DATED 4-16-79.

## Chemical Properties

HCC: N1

Boiling Pt: B.P. Text: 550-750F

Vapor Pres: NIL

Vapor Density: 8.9

Spec Gravity: 0.878

Evaporation Rate & Reference: Solubility in Water: NEG

Appearance and Odor: WATER WHITE COLORED LIQUID, SLIGHT PETROLEUM ODOR.

Percent Volatiles by Volume: NEG

## Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDANTS: LIQ CHLORINE, CONC O<sub>2</sub>, SODIUM, ETC.

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: FUME, SMOKE, CO, SULFUR OXIDES

## Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.