UNIVOLT N 61

MSDS Number

BBDFY

National Stock Number

9160-00D000731

Product Name

UNIVOLT N 61

Manufacturer

EXXON CO USA

Product Identification

Product ID:UNIVOLT N 61
MSDS Date:01/01/1987
FSC:9160
NIIN:00D000731
MSDS Number: BBDFY

Responsible Party

EXXON CO, USA.

Emergency Phone: 713-656-3424

Cage: EO029

Contractor

EXXON COMPANY U.S.A.

HOUSTON, TX 77252-2180

US

713-656-5949 / 713-656-3424

Cage: 29700

Ingredients

PETROLEUM HYDROCARBON

Hazards

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION.

First Aid

First Aid:SKIN:WASH W.SOAP & H*2O. EYES:FLUSH W. H*2O. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Flash Point:320F/160C(COC)
Lower Limits:1
Upper Limits:7
Extinguishing Media:SM:CO*2, DRY CHEM. LG:H*2O SPRAY,FOG OR FOAM
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

Accidental Release

Spill Release Procedures:RECOVER FREE LIQ.ADD ABSORBENT TO SPILL AREA.KEEP PETROLEUM PRODUCTS OUT OF SEWER & WATERCOURSES BY DIKING OR IMPOUNDING.ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY

ENTER SEWERS,WATERCOURSES.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.
Other Precautions:REMOVE OIL-SOAKED CLOTHING & LAUNDER BEFORE RE-USE.

Exposure Controls

Respiratory Protection:NORMALLY NONE
Ventilation:LOCAL EXHAUST & > 60 FPM HOOD OR FACE VELOCITY.
Protective Gloves:CHEM-RESISTANT
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:CHEM-RESIST APRON OR CLOTHING.
Supplemental Safety and Health
MSDS DATED 4-16-79.

Chemical Properties

HCC:N1
Boiling Pt:B.P. Text:550-750F
Vapor Pres:NIL
Vapor Density:8.9
Spec Gravity:0.878
Evaporation Rate & Reference:Solubility in Water:NEG
Appearance and Odor:WATER WHITE COLORED LIQUID,SLIGHT PETROLEUM ODOR.
Percent Volatiles by Volume:NEG

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS:LIQ CHLORINE,CONC O*2,SODIUM,ETC.
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:FUME,SMOKE,CO,SULFUR OXIDES

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.