

SPRAYWAY BEE WASP HORNET KILLER, #780829

MSDS Number

BBDHJ

National Stock Number

6840-01-112-4913

Product Name

SPRAYWAY BEE WASP HORNET KILLER, #780829

Manufacturer

SPRAYWAY INC

Product Identification

Product ID: SPRAYWAY BEE WASP HORNET KILLER, #780829

MSDS Date: 07/19/1984

FSC: 6840

NIIN: 01-112-4913

MSDS Number: BBDHJ

Responsible Party

SPRAYWAY, INC.

484 VISTA AVE

ADDISON 60101

US

Emergency Phone: 312-628-0998

Cage: FO362

Contractor

SPRAYWAY, INC.

ADDISON, IL 60101

US

(800) 228-5635

Cage: FO362

Ingredients

PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT)

CAS: 8002-05-9

RTECS: SE7449000

Fraction By Weight: 85%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 8990

MALATHION (SARA III)

CAS: 121-75-5

RTECS: WM8400000

Fraction By Weight: 2%

OSHA PELS, 15 MG/M3

ACGIH TLV: S, 10 MG/M3; 9293

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

DICHLORVOS (DDVP) (SARA III)

CAS: 62-73-7

RTECS: TC0350000

Fraction By Weight: 0.2%

OSHA PELs, 1 MG/M3

ACGIH TLV: S, 0.1 MG/M3; 9192

EPA Report Quantity: 10 LBS

DOT Report Quantity: 10 LBS

PYRETHRUM (SARA III)

CAS: 8003-34-7

RTECS: UR4200000

Fraction By Weight: 0.1%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

LIQUEFIED PETROLEUM GAS (LPG)-PROPELLANT

CAS: 68476-85-7

RTECS: OJ2200000

Fraction By Weight: 10%.

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

Hazards

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:NONE LISTED BY MFR
Effects of Overexposure:EYE,SKIN:
IRRIT,REDNESS,ABSORB.INHL:RHINITIS,HEADACHE,TIGHT
CHEST,WHEEZING,LARYNGEAL SPASM,SALIVATION.
INGEST:ANOREXIA,NAUS,VOMIT,ABDOM CRAMP,DIARR,ATAXIA.
Medical Cond Aggravated by Exposure:NONE GIVEN

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point:N/R-AEROSOL
Extinguishing Media:DRY CHEMICAL, CO*2.
Fire Fighting Procedures:KEEP CONTAINERS COOL. USE PROTECTIVE SHIELDING
OR EQUIPMENT AS REQ'D AGAINST BURSTING, RUPTURING OR VENTING
CONTAINERS.
Unusual Fire/Explosion Hazard:ABOVE 130F, CONTAINERS MAY VENT, RUPTURE
OR BURST!

Accidental Release

Spill Release Procedures: AVOID INHL VAPORS, SKN CONTACT. WEAR SCBA PP MODE OR CCROV RESP. REMOVE IGNITION SOURCES, VENTILATE AREA TO DISSIPATE GASES & VAPORS. COLLECT RESIDUE W/ABSORBENT, DISPOSE TO CLOSABLE CONTAINERS.

Handling

Handling and Storage Precautions: DO NOT STORE ABOVE 130F.

Other Precautions: NONE GIVEN.

Exposure Controls

Ventilation: NONE

Protective Gloves: NONE

Eye Protection: SAFETY GLASSES, GOGGLES.

Other Protective Equipment: NONE

Supplemental Safety and Health

Chemical Properties

HCC: V3

Vapor Pres: NR-AEROSOL

Vapor Density: >1

Evaporation Rate & Reference: Solubility in Water: NEG

Appearance and Odor: HEAVY JET STREAM SPRAY, PETROLEUM DISTILLATE ODOR.

Percent Volatiles by Volume: 95

Stability

Stability Indicator/Materials to Avoid: YES

NONE

Stability Condition to Avoid: NONE

Hazardous Decomposition Products: OXIDES OF CARBON, PHOSPHOROUS, SULFUR,

HCL POSS.

Disposal

Waste Disposal Methods: DEPRESSURIZE & LANDFILL IAW ALL LAWS & REGS. DO NOT PUNCTURE OR INCINERATE EMPTY CONTRS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.