

E115, EFFECTO ENAMEL GRENADIER RED

MSDS Number

BBDHN

National Stock Number

8010-00D000773

Product Name

E115, EFFECTO ENAMEL GRENADIER RED

Manufacturer

PRATT AND LAMBERT INC

Product Identification

Product ID:E115, EFFECTO ENAMEL GRENADIER RED

MSDS Date:09/12/1985

FSC:8010

NIIN:00D000773

MSDS Number: BBDHN

Responsible Party

PRATT & LAMBERT INC.

75 TONAWANDA ST.

BUFFALO 14240

US

Emergency Phone: 716-873-6000

Cage: 77359

Contractor

PRATT & LAMBERT

BUFFALO, NY 14240

US

716-873-6000

Cage: 77359

Ingredients

MINERAL SPIRITS(40-50%),(INCLUDING VERY SMALL AMOUNT OF

Fraction By Weight: 45%

OSHA PEL500 PPM

ACGIH TLV: 500 PPM

METHYL ETHYL KETOXIME (2-BUTANONE,OXIME)

CAS: 96-29-7

RTECS: EL9275000

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Effects of Overexposure:INH:ANESTHETIC,IRRITATION OF NOSE,THROAT,EYES &
POSSIBLE DIZZINESS & NAUSEA.

First Aid

First Aid:SKIN:WASH W.SOAP & H*20. EYES:FLUSH W. H*20. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Flash Point Method:TCC
Flash Point:104F/40C
Extinguishing Media:CO*2, FOAM, DRY CHEM.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO VERY HOT SURFACES.

Accidental Release

Spill Release Procedures:REMOVE SOURCES OF IGNITION. VENTILATE AREA & AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT & NON-SPARKING TOOLS. STEPS MUST BE TAKEN TO PREVENT CONTAMINATION OF GROUND WATER OR STREAMS.

Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. CONTAINERS SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER.
Other Precautions:DO NOT WELD OR CUT ON EMPTY CONTAINERS. DO NOT USE UNTIL ALL SAFETY PRECAUTIONS & MIXING DIRECTIONS HAVE BEEN READ & FULLY UNDERSTOOD BY THE USER.

Exposure Controls

Respiratory Protection:OUTDOOR OR OPEN AREAS:USE NIOSH-APPROVED MECHANICAL RESPIRATOR; IN RESTRICTED VENTILATION AREA:USE NIOSH-APPROVED CHEMICAL-MECHANICAL FILTERS DESIGNED TO REMOVE SPRAY MIST & ORGANIC VAPORS.
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV LEVEL.
Protective Gloves:SOLVENT IMPERMEABLE.
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:USE PROTECTIVE EQUIPMENT TO PREVENT SKIN CONTACT.
Supplemental Safety and Health

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Density:>AIR
Spec Gravity:0.936
Evaporation Rate & Reference:Percent Volatiles by Volume:55

Stability

Stability Indicator/Materials to Avoid:YES
AVOID STRONG ACIDS OR ALKALINE MATERIALS.
Stability Condition to Avoid:AVOID FIRES, HEAT, & HOT SURFACES.
Hazardous Decomposition Products:BURNING WILL PRODUCE SMOKE & OXIDES OF CARBON.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. INCINERATE IN EPA APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

