

LUBRIPLATE APG 140

MSDS Number

BBDHV

National Stock Number

9150-00D000779

Product Name

LUBRIPLATE APG 140

Manufacturer

FISKE BROTHERS REFINING CO

Product Identification

Product ID:LUBRIPLATE APG 140

MSDS Date:05/01/1987

FSC:9150

NIIN:00D000779

MSDS Number: BBDHV

Responsible Party

FISKE BROTHERS REFINING CO.

1500 OAK-DALE AVE, STATION A

TOLEDO , OH 43605-3843

US

Emergency Phone: 201-589-9150

Info Phone: 201-589-9150

Preparer: ROBERT J. SIBILIA

Cage: 9N579

Contractor

FISKE BROTHERS REFINING CO

TOLEDO, OH 43605

US

419-691-2491

Cage: 9N579

Ingredients

MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS: 8012-95-1

RTECS: PY8030000

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3/10 STEL;9192

ADDITIVES

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:IRRITATION OF EYES,SKIN AND RESPIRATORY TRACT. CHRONIC:DERMATITIS,MILD TO SEVERE PULMONARY EDEMA,DUE TO INGESTION.

Effects of Overexposure:SEE HEALTH HAZARDS DATA.

Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE

WORSEN.

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER FOR 15 MINUTES;CONSULT A PHYSICIAN. SKIN:WASH WITH SOAP & WATER. INHALATION:REMOVE TO FRESH AIR,CALL A PHYSICIAN. INGESTION:CALL A PHYSICIAN IMMEDIATELY. DO NOT INDUCE VOMITING.

Fire Fighting

Flash Point Method:COC
Flash Point:360-405F
Lower Limits:0.9
Upper Limits:7.0
Extinguishing Media:CO*2,WATER MIST,FOAM.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:DO NOT CUT,DRILL,GRIND OR WELD,AS THEY MAY EXPLODE

Accidental Release

Spill Release Procedures:NORMAL CLEANUP WITH USE OF "OIL DRI" OR ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:STORE AT NORMAL ROOM TEMP PREFERRED.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL.
Ventilation:LOCAL EXHAUST/GENERAL TO MAINTAIN PEL/TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES
Other Protective Equipment:PROTECTIVE CLOTHING AND EYE-WASH
Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;DO NOT BREATHE VAPORS/MIST;DO NOT USE CONTAMINATED CLOTHES,WASH THOROUGHLY AFTER USE.
Supplemental Safety and Health
MSDS DATED 10-14-85

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:>550F/288C
Vapor Pres:Vapor Density:>5.0
Spec Gravity:0.88-0.93
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:TRANSPARENT AMBER OIL WITH ADDITIVE ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:MAY FORM SO*2,INCOMPLETE COMBUSTION,CO GAS.

Disposal

Waste Disposal Methods:INCINERATE OR APPROVED WASTE DISPOSAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.