

GOLIATH PEN OIL (AEROSOL)

MSDS Number

BBDMH

National Stock Number

5970-00D000879

Product Name

GOLIATH PEN OIL (AEROSOL)

Manufacturer

MALTER INTERNATIONAL INC

Product Identification

Product ID: GOLIATH PEN OIL (AEROSOL)

MSDS Date: 01/01/1987

FSC: 5970

NIIN: 00D000879

MSDS Number: BBDMH

Responsible Party

MALTER INTERNATIONAL, INC.

80 FIRST STREET

GRETN, LA 70053

US

Emergency Phone: 504-362-3232

Info Phone: 504-362-3232

Cage: 27978

Contractor

MALTER INTERNATIONAL BULK CHEMICAL DIVISION

GRETN, LA 70053

US

504-362-3232, OR 800-535-4095

Cage: 27978

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 27.5%

OSHA PEL100 PPM

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 37.5%

OSHA PEL350 PPM/450 STEL

ACGIH TLV: 350 PPM/450 STEL; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

N-AMYL ACETATE (SARA III)

CAS: 628-63-7

RTECS: AJ1925000

Fraction By Weight: 2.5%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 9.5%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

8-11%)

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 9.5%

Hazards

Effects of Overexposure: HEADACHE ONLY EFFECT GIVEN.

First Aid

First Aid: INHAL: RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE: IMMED FLUSH W/PLENTHY OF WATER. SKIN: WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST: DO NOT INDUCE VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Lower Limits: 0.9

Upper Limits: 15.0

Extinguishing Media: CO*2, FOAM DRY CHEMICAL

Fire Fighting Procedures: DO NOT USE WATER JET.

Unusual Fire/Explosion Hazard: AEROSOL. CONTENTS UNDER PRESSURE

Accidental Release

Spill Release Procedures: FOR LIQUID, COLLECT W/ABSORBENT, PLACE IN CLOSABLE CONTAINERS. VENTILATE AREA, REMOVE ALL HEAT & IGNITION SOURCES.

Handling

Handling and Storage Precautions: STORE IN COOL, DRY, SHADED AREA. DO NOT USE IN PRESENCE OF HEAT, SPARKS, OPEN FLAME. DO NOT EXCEED 120F STORAGE TEMPERATURE.

Other Precautions: HANDLE CAREFULLY-CONTENTS UNDER PRESSURE.

Exposure Controls

Respiratory Protection: NONE

Ventilation: LOCAL EXHAUST.

Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES,SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health
MSDS NON-OSHA DTD JUL84. TLV SET AT 350 PPM BY DOD/DGSC BASED ON
INGREDIENTS LISTED BY MFR.

Chemical Properties

HCC:V3
Appearance and Odor:BROWN LIQUID, WINTERGREEN ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS, ALKALIS.
Stability Condition to Avoid:AVOID EXCESS HEAT, IGNITION SOURCES.
Hazardous Decomposition Products:CARBON OXIDES

Disposal

Waste Disposal Methods:INCINERATE IAW ALL LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.