



186 5849,EKTAPRINT 2 BLEACH-FIX,PART B

MSDS Number

BBDPB

National Stock Number

6750-00D000938

Product Name

186 5849,EKTAPRINT 2 BLEACH-FIX,PART B

Manufacturer

EASTMAN KODAK COMPANY

Product Identification

Product ID:186 5849,EKTAPRINT 2 BLEACH-FIX,PART B

MSDS Date:04/20/1983

FSC:6750

NIIN:00D000938

MSDS Number: BBDPB

Responsible Party

EASTMAN KODAK COMPANY

343 STATE STREET

ROCHESTER , NY 14650

US

Emergency Phone: 716-722-5151

Info Phone: 716-722-5151

Cage: 19139

Contractor

EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

ROCHESTER, NY 14650-1115

US

716-722-5151/(800) 242-2424

Cage: 19139

Ingredients

AMMONIUM((ETHYLENEDINITRILLO)TETRAACETO)-FERRATE (III); WT %

CAS: 21265-50-9

Fraction By Weight: 42.5%

1-5% (CAS # & NIOSH # OF AMMONIUM

CAS: 1336-21-6

RTECS: BQ9625800

Fraction By Weight: 03.0%

OSHA PEL50PPM

ACGIH TLV: 25PPM

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS



45-55%

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 50.0%

Hazards

LD50 LC50 Mixture:LD50 ORL RAT:0.5 - 5.0 G/KG
Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

First Aid

First Aid:IN CASE OF CONTACT,FLUSH AREAS WITH PLENTY OF WATER.

Fire Fighting

Flash Point:NONE
Extinguishing Media:USE EXTINGUISHING MEDIA SUITABLE FOR SURROUNDING FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING TO PREVENT CONTACT WITH SKIN & EYES.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF DECOMPOSITION PRODUCTS.

Accidental Release

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER.

Handling

Handling and Storage Precautions:AVOID CONTACT WITH METALS.

Exposure Controls

Respiratory Protection:NONE
Ventilation:MECHANICAL RECOMMENDED.
Protective Gloves:NONE
Eye Protection:NONE
Other Protective Equipment:NONE
Supplemental Safety and Health
THIS ENTRY DESCRIBES PART B OF EKTAPRINT BLEACH-FIX; EXACTLY SAME DATA DESCRIBED UNDER 2 OR 3 DIFFERENT NSNS WHICH ARE THE KITS. WHEN THIS PRODUCT PLACED IN A KIT,THE KIT'S CAT NO WILL BE APPLICABLE. SEE KITS NSNS: 6750-01-068-0727, 6750-01-047-5477 & 6750-01-214-4621.

Chemical Properties

HCC:C3
Boiling Pt:B.P. Text:>212F/>100C
Vapor Pres:18
Vapor Density:0.6
Spec Gravity:1.29
pH:7.0
Solubility in Water:COMPLETE
Appearance and Odor:OPAQUE,REDDISH-BROWN SOLN;SLIGHT AMMONIACAL ODOR.
Percent Volatiles by Volume:55%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG ACIDS & ALKALI
Stability Condition to Avoid:HEAT,HIGH TEMPERATURES
Hazardous Decomposition Products:AMMONIA

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):



This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.