



---

## **INNERBOND 1440F**

### **MSDS Number**

BBDPY

### **National Stock Number**

6850-00D000961

### **Product Name**

INNERBOND 1440F

### **Manufacturer**

INLAND PACKING INC

### **Product Identification**

Product ID:INNERBOND 1440F  
MSDS Date:01/01/1987  
FSC:6850  
NIIN:00D000961  
MSDS Number: BBDPY

### **Responsible Party**

INLAND PACKING,INC.

Emergency Phone: 502-737-6757

Cage: EO068

### **Contractor**

INLAND PACKING,INC.

644

ELIZABETHTOWN, KY 42701-9804

US

502-737-6757

Cage: EO068

### **Ingredients**

POLYDIMETHYLSILOXANE(CAS#63148-62-9)

CAS: 9016-00-6

RTECS: TQ2690000

INERT FILLERS

### **Hazards**

Effects of Overexposure:LOW TOXICITY.NO REPORTED ADVERSE REACTIONS;CAN CAUSE TRANSIENT IRRITATION.

### **First Aid**

First Aid:SKIN:WASH W.SOAP & H\*2O EYES:FLUSH W. H\*2O. INGESTED:GIVE 2 GLASSES H\*2O; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH.

### **Fire Fighting**

Flash Point:>200F/93C(TCC)  
Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*2O FOG.  
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP  
Unusual Fire/Explosion Hazard:NONE



---

## Accidental Release

Spill Release Procedures:SWEEP UP INTO A STEEL DRUM.SRAPE RESIDUE FROM CONTAMINATED AREAS & WASH WITH SOLVENT.

## Handling

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED,LOW FIRE RISK AREA. PROTECT FR HEAT,SHOCK KEEP CONTAINERS CLOSED.  
Other Precautions:AVOID BREATHING VAPORS OR MIST.WASH HANDS THOROUGHLY AFTER HANDLING.DO NOT EAT,DRINK OR SMOKE IN THE WORK AREA.

## Exposure Controls

Respiratory Protection:NONE  
Ventilation:NEED ADEQUATE VENTILATION, & LOCAL EXHAUST.  
Protective Gloves:YES  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:SAFETY SHOWER & EYE BATH  
Supplemental Safety and Health  
MSDS DATED 4-29-86.

## Chemical Properties

HCC:N1  
Spec Gravity:1.036  
Solubility in Water:INSOLUBLE  
Appearance and Odor:TRANSLUCENT-WHITE/SLIGHT ETHYLATED PASTE.

## Stability

Stability Indicator/Materials to Avoid:YES  
MINERAL ACID.STRONG BASE, & AIR DURING VULCANIZATION.  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:SILICA & CARBON OXIDES FROM COMBUSTION; OR LIGHT ALCOHOLS.

## Disposal

Waste Disposal Methods:BURY IN A SECURE LANDFILL ACCORDING TO LOCAL,STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.