

# **INNERBOND 1440F**

### **MSDS Number**

**BBDPY** 

#### **National Stock Number**

6850-00D000961

### **Product Name**

**INNERBOND 1440F** 

#### Manufacturer

INLAND PACKING INC

### **Product Identification**

Product ID:INNERBOND 1440F MSDS Date:01/01/1987 FSC:6850 NIIN:00D000961 MSDS Number: BBDPY

# **Responsible Party**

INLAND PACKING, INC.

Emergency Phone: 502-737-6757

Cage: E0068

Contractor

#### \_\_\_\_\_

INLAND PACKING, INC.

644

US

ELIZABETHTOWN, KY 42701-9804

502-737-6757

Cage: EO068

### **Ingredients**

POLYDIMETHYLSILOXANE(CAS#63148-62-9)

CAS: 9016-00-6 RTECS: TQ2690000

**INERT FILLERS** 

### **Hazards**

Effects of Overexposure:LOW TOXICITY.NO REPORTED ADVERSE REACTIONS;CAN CAUSE TRANSIENT IRRITATION.

# First Aid

First Aid:SKIN:WASH W.SOAP & H\*20 EYES:FLUSH W. H\*20. INGESTED:GIVE 2 GLASSES H\*20; INDUCE VOMITING.CALL A PHYSICIAN. INHALE:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. IF UNCONS DO NOT TAKE ANYTHING BY MOUTH.

# **Fire Fighting**

Flash Point:>200F/93C(TCC) Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*20 FOG. Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP Unusual Fire/Explosion Hazard:NONE



#### **Accidental Release**

Spill Release Procedures: SWEEP UP INTO A STEEL DRUM. SCRAPE RESIDUE FROM CONTAMINATED AREAS & WASH WITH SOLVENT.

### Handling

Handling and Storage Precautions: STORE IN COOL, DRY WELL VENTED, LOW FIRE RISK AREA. PROTECT FR HEAT, SHOCK KEEP CONTAINERS CLOSED.

Other Precautions: AVOID BREATHING VAPORS OR MIST. WASH HANDS THOROUGHLY AFTER HANDLING. DO NOT EAT, DRINK OR SMOKE IN THE WORK AREA.

# **Exposure Controls**

Respiratory Protection: NONE
Ventilation: NEED ADEQUATE VENTILATION, & LOCAL EXHAUST.
Protective Gloves: YES
Eye Protection: SAFETY GLASSES
Other Protective Equipment: SAFETY SHOWER & EYE BATH
Supplemental Safety and Health
MSDS DATED 4-29-86.

## **Chemical Properties**

HCC:N1 Spec Gravity:1.036 Solubility in Water:INSOLUBLE Appearance and Odor:TRANSLUCENT-WHITE/SLIGHT ETHYLATED PASTE.

## **Stability**

Stability Indicator/Materials to Avoid:YES MINERAL ACID.STRONG BASE, & AIR DURING VULCANIZATION. Stability Condition to Avoid:NONE Hazardous Decomposition Products:SILICA & CARBON OXIDES FROM COMBUSTION; OR LIGHT ALCOHOLS.

#### Disposal

Waste Disposal Methods: BURY IN A SECURE LANDFILL ACCORDING TO LOCAL, STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.