

## **NCR TAN LAC (TYPEWRITER PAINT-AEROSOL)**

### **MSDS Number**

BBDQG

### **National Stock Number**

8010-00D000968

### **Product Name**

NCR TAN LAC (TYPEWRITER PAINT-AEROSOL)

### **Manufacturer**

AMES SUPPLY CO

### **Product Identification**

Product ID:NCR TAN LAC (TYPEWRITER PAINT-AEROSOL)

MSDS Date:01/01/1987

FSC:8010

NIIN:00D000968

MSDS Number: BBDQG

### **Responsible Party**

AMES SUPPLY CO.

Emergency Phone: (312)964-2440

Cage: EO069

### **Contractor**

AMES SUPPLY CO.

Cage: EO069

### **Ingredients**

ETHYL ETHOXYPROPIONATE,CAS#763-69-9

CAS: 763-69-9

RTECS: UF3325000

Fraction By Weight:

ACGIH TLV: 50PPM(MFR)

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 25%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 15%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Effects of Overexposure:ANESTH;IRR.TO SKIN,UPPR  
RESP.SYS;LIGHT-HEAD;STAGGERNG GAIT;GIDD;NAUSEA;HARMFUL/FATAL IF  
SWALLOWED.

## First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG  
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE  
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

## Fire Fighting

Flash Point:N/R,AEROSOL  
Extinguishing Media:CO\*2, FOAM, DRY CHEM.  
Fire Fighting Procedures:WTR MAY BE INEFFECT-USE WTR TO KEEP FIRE EXPSD  
CONT.COOL.  
Unusual Fire/Explosion Hazard:DO NOT SPRAY NEAR OPEN FLAME.KEEP AT ROOM  
TEMP.AS EXPSRE TO DIRECT SUNLIGHT,OTHER HEAT,CAUSES BURST.

## Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA  
WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS  
SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING  
TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.KEEP AT ROOM  
TEMP.

## Exposure Controls

Respiratory Protection:NIOSH APPVD RESP.IF TLV IS EXCEEDED.  
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES  
Other Protective Equipment:NONE SPECIFIED

Supplemental Safety and Health  
MSDS DATED 01-03-86/OTHER INGRED:METHYLENE CHLORIDE,PROPANE

## Chemical Properties

HCC:V3  
Boiling Pt:B.P. Text:Vapor Density:>1  
Evaporation Rate & Reference:>1(ETHER=1)  
Percent Volatiles by Volume:94

## Stability

Stability Indicator/Materials to Avoid:YES  
NONE SPECIFIED  
Stability Condition to Avoid:DO NOT STORE ABOVE 120F  
Hazardous Decomposition Products:CO,CO\*2,HCL

## Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.--DO NOT  
INCINERATE--

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.