

## **AMES QUICK SPRAY WRINKLE PAINT - ALL COLORS**

### **MSDS Number**

BBDQJ

### **National Stock Number**

5970-00D000970

### **Product Name**

AMES QUICK SPRAY WRINKLE PAINT - ALL COLORS

### **Manufacturer**

ILLINOIS BRONZE POWDER AND PAINT COMPANY

### **Product Identification**

Product ID:AMES QUICK SPRAY WRINKLE PAINT - ALL COLORS

MSDS Date:01/01/1987

FSC:5970

NIIN:00D000970

MSDS Number: BBDQJ

### **Responsible Party**

ILLINOIS BRONZE POWDER & PAINT COMPANY

300 EAST MAIN STREET

LAKE ZURICH , IL 60047-2580

US

Emergency Phone: 800-228-5635

Info Phone: 312-488-8001

Cage: 91794

### **Contractor**

ILLINOIS BRONZE PAINT COMPANY

LAKE ZURICH, IL 60047-2580

US

800-228-5635

Cage: 91794

### **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 15 - 20%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPYLENE GLYCOL MONOMETHYL ETHER

CAS: 107-98-2

RTECS: UB7700000

Fraction By Weight:

OSHA PEL100 PPM/150 STEL  
ACGIH TLV: 100 PPM/150STEL;9192

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 35%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 10 - 23%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 10%

ACGIH TLV: 1000 PPM

## Hazards

Effects of Overexposure:ANESTHETIC,IRRITATING TO RESPIRATOR  
SYS;HEADACHE,DIZZINESS,UNCONSCIOUS OR COMA.

## First Aid

First Aid:INH:REMOVE FROM EXPOSURE;EYE:FLUSH W/LARGE QUANTITIES OF  
WATER FOR 15 MIN;SKIN:WIPE OFF W/TOWEL. REMOVE REMAINDER WITH  
MINERAL SPIRITS,TURPENTINE OR LACQUER THINNER.IN CASE OF A  
LACQUER,WASH WITH SOAP & WATER.REMOVE CONTAMINATED CLOTHING.

## Fire Fighting

Extinguishing Media:CO\*2, FOAM, DRY CHEM.

Fire Fighting Procedures:COOL CONTR W. WATER. APPLY FROM DISTANCE.  
AVOID END OF TK.

Unusual Fire/Explosion Hazard:CANS WILL RUPTURE FROM INTERNAL PRESSURE  
AT ABOUT 190F & DISCHARGE FLAMMABLE CONTENTS.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING  
VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT.

## Handling

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
QUANTITIES IN BULIDINGS DESIGNED & PROTECTED FOR STORAGE OF NFPA  
CLASS 1A FLAM.LIQ.

## Exposure Controls

Respiratory Protection:NONE  
Ventilation:GENERAL VENTILATION  
Protective Gloves:NONE  
Eye Protection:NONE  
Other Protective Equipment:NONE  
Supplemental Safety and Health  
MSDS DATED 5-22-74.

## **Chemical Properties**

HCC:V3  
Boiling Pt:B.P. Text:Vapor Density:>1  
Evaporation Rate & Reference:>1,ETHER=1  
Percent Volatiles by Volume:85

## **Stability**

Stability Indicator/Materials to Avoid:YES  
NONE  
Stability Condition to Avoid:NONE  
Hazardous Decomposition Products:HCL,CO,PHOSGENE

## **Disposal**

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &  
DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE  
INTERNATIONAL,FEDERAL,STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.