

https://msdsreport.com/msds/BBDRC

# **DIAMOND OR CUBIC BORON NITRIDE GRINDING WHE**

# **MSDS Number**

BBDRC

# **National Stock Number**

3415-00D000987

# **Product Name**

DIAMOND OR CUBIC BORON NITRIDE GRINDING WHE

### Manufacturer

PERMATTACH DIAMOND TOOL CORP

# **Product Identification**

Product ID:DIAMOND OR CUBIC BORON NITRIDE GRINDING WHE MSDS Date:01/01/1987 FSC:3415 NIIN:00D000987 MSDS Number: BBDRC

# **Responsible Party**

PERMATTACH DIAMOND TOOL CORP.

Emergency Phone: (603)673-2904

Cage: 9H171

# Contractor

PERMATTACH DIAMOND TOOL CORP.

Cage: 9H171

# Ingredients

PHOSPHOROUS (YELLOW) (SARA III)

CAS: 7723-14-0

- RTECS: TH3500000
- OSHA PEL0.1 MG/M3
- ACGIH TLV: 0.1 MG/M3; 9192
- EPA Report Quantity: 1 LB
- DOT Report Quantity: 1 LB

COPPER (SARA III) CAS: 7440-50-8 RTECS: GL5325000 OSHA PEL0.1MG/M3 FUME/1 DUST ACGIH TLV: 0.2MG/M3 FUME; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

GRAPHITE,CAS#7882-42-5 RTECS: VV7780000 ACGIH TLV: 5MG/CUM(MFR)



•

CALCIUM OXIDE CAS: 1305-78-8 RTECS: EW3100000 OSHA PEL5 MG/M3 ACGIH TLV: 2 MG/M3; 9192

NICKEL (SARA III)

CAS: 7440-02-0

RTECS: QR5950000

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

#### Hazards

Effects of Overexposure:EYES/SKIN:IRR;INH:COUGH,SHORTNESS OF BREATH.

#### **First Aid**

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET. ING:GET MEDICAL ATTENTION.

#### **Fire Fighting**

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Unusual Fire/Explosion Hazard:NONE

#### **Accidental Release**

Spill Release Procedures:SWEEP UP AND PLACE IN SUITABLE DISPOSAL CONTAINER.

#### Handling

Handling and Storage Precautions: NONE

#### **Exposure Controls**

Respiratory Protection:NIOSH/MSHA APPVD RESP. Ventilation:LOCAL EXHAUST & GENERAL MECH.VENTIL.TO KEEP BELOW TLV. Protective Gloves:AS REQUIRED Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:HEARING PROTECTION. Supplemental Safety and Health MSDS 11-25-85/OTHER INGRED:SILICON CARBIDE,ALUMINUM OXIDE,WOLLASTONITE,TITANIUM OXIDE,CHROMIUM OXIDE/

#### **Chemical Properties**

HCC:N1 Spec Gravity:2.5 Solubility in Water:SLIGHT Appearance and Odor:SOLID PRODUCT MAY GIVE OFF SLIGHT ODOR IN USE.

#### Stability

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED Stability Condition to Avoid:NONE SPECIFIED Hazardous Decomposition Products:DUST FROM GRINDING WHEEL-COOLANT DECOMPOSITION PRODUCTS

#### Disposal

Waste Disposal Methods:SM & LG SPILL:DEPOSIT IN A POSTED TOXIC SUBSTANCE LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS



Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.