

# CALCIUM, TOTAL HARDNESS 10000 MG/L:CAT# 2187

# **MSDS Number**

**BBDVJ** 

## **National Stock Number**

6810-00D001081

### **Product Name**

CALCIUM, TOTAL HARDNESS 10000 MG/L:CAT# 2187

#### Manufacturer

HACH COMPANY

# **Product Identification**

Product ID:CALCIUM, TOTAL HARDNESS 10000 MG/L:CAT# 2187

MSDS Date: 01/01/1987

FSC:6810

NIIN:00D001081 MSDS Number: BBDVJ

# **Responsible Party**

HACH COMPANY

Emergency Phone: (515) 232-2533

Cage: 4T252

# **Contractor**

HACH COMPANY

907

US

AMES, IA 50010

800-227-4224

Cage: 4T252

### **Ingredients**

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight:

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

HYDROGEN CHLORIDE (HYDROCHLORIC ACID) (SARA III)

CAS: 7647-01-0 RTECS: MW4025000 Fraction By Weight: OSHA PELC 5 PPM

ACGIH TLV: C 5 PPM; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS



UNIDENTIFIED COMPONENTS

Fraction By Weight:

WATER; CAS\$7732-18-5

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: >90%

#### **Hazards**

Effects of Overexposure: EYES/SKIN: CAUSES IRRITATION; INGEST: MAY IRRIT GI TRACT, DIARR ETC; INHALATION: VAP MAY CAUSE IRRIT.

#### First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

### Fire Fighting

Flash Point: NONE

Extinguishing Media: EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE Fire Fighting Procedures: WEAR SELF-CNTD BRTHG, APP H\*20 SPRAY TO COOL CONTR

Unusual Fire/Explosion Hazard: NONE NOTED BY MANUFACTURER.

#### **Accidental Release**

Spill Release Procedures: USE APPROPRIATE PROTECTIVE EQUIP DURING CLEAN UP; COVER CONTAMINATED LIQ/SURFACE WITH SODA ASH OR SODIUM BICARBONATE.MIX & ADD WATER. FLUSH DOWN TO DRAIN WITH LG QTY OF WATER.

### Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions: AVOID PROLONGED/REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH EYES. WASH THOROUGHLY AFTER HANDLING.

# **Exposure Controls**

Respiratory Protection: NONE SHOULD BE NEEDED

Ventilation: MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE

**VENTILATION** 

Protective Gloves: DISPOSABLE Eye Protection: SAFETY GLASSES

Other Protective Equipment: NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

MSDS FROM HACH COMPANY EFFECTIVE:11/22/85; PH RANGES FROM 3.9 TO 4.0

### **Chemical Properties**

HCC:N1

Boiling Pt:B.P. Text:212F/100C

Spec Gravity: 0.998

Solubility in Water: COMPLETE

Appearance and Odor: CLEAR, COLORLESS LIQUID

# Stability

Stability Indicator/Materials to Avoid:YES NOT KNOWN Stability Condition to Avoid:EXCESSV HEAT Hazardous Decomposition Products:NOT KNOWN

#### Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE



INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.