



BUTANE (LIQUIFIED GAS UNDER PRESSURE)

MSDS Number

BBDVS

National Stock Number

6830-00D001091

Product Name

BUTANE (LIQUIFIED GAS UNDER PRESSURE)

Manufacturer

UNION CARBIDE CORP

Product Identification

Product ID: BUTANE (LIQUIFIED GAS UNDER PRESSURE)

MSDS Date: 01/01/1987

FSC: 6830

NIIN: 00D001091

MSDS Number: BBDVS

Responsible Party

UNION CARBIDE CORPORATION

270 PARK AVE.

NEW YORK, NY 10017

US

Emergency Phone: 304-744-3487

Info Phone: 304-744-3487

Cage: 36346

Contractor

UNION CARBIDE CORP LINDE DIV

DANBURY, CT 06817-0001

US

800-822-4357; 304-744-3487

Cage: 36346

Ingredients

BUTANE

CAS: 106-97-8

RTECS: EJ4200000

Fraction By Weight: 100%

OSHA PEL800 PPM

ACGIH TLV: 800 PPM; 9192

Hazards

LD50 LC50 Mixture: TLV IS 600PPM TWA

Routes of Entry: Inhalation: YES Skin: NO Ingestion: NO

Reports of Carcinogenicity: NTP: NO IARC: NO OSHA: NO

Health Hazards Acute and Chronic: N-BUTANE GAS IS A SIMPLE ASPHYXIAN. OVEREXPOSURE MAY CAUSE CNS DEPRESSION.

Explanation of Carcinogenicity: THERE ARE NO INGREDIENTS ABOVE 0.1% WHICH ARE IDENTIFIED AS CARCINOGENS BY NTP, IARC OR OSHA.

Effects of Overexposure: INHAL: ASPHYXIATION, ANESTHESIA

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.



First Aid

First Aid: REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEEDED. KEEP WARM AND AT REST. AVOID ADMINISTRATION OF EPINEPHRINE, OTHER SYMPATHOMIMETIC AMINES.

Fire Fighting

Flash Point: -76F, -60C, TCC
Autoignition Temp: Autoignition Temp Text: 761F
Lower Limits: 1.9
Upper Limits: 8.5
Extinguishing Media: CO₂, DRY CHEM, WATER SPRAY, WATER FOG.
Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS/FULL PROTECTIVE EQUIPMENT. COOL FIRE EXPOSED CONTAINERS WITH WATER FOG. DO NOT EXTINGUISH FLAME; ALLOW FIRE TO SELF-EXTINGUISH.
Unusual Fire/Explosion Hazard: **FLAMABLE GAS** CONTAINERS MAY BURST AT ELEVATED TEMPERATURES. DO NOT EXTINGUISH FLAMES; THEY MAY REIGNITE EXPLOSIVELY. FORMS EXPLOSIVE MIXTURE W/AIR+OXIDIZERS.

Accidental Release

Spill Release Procedures: ELIMINATE SOURCES OF IGNITION. USE PROPER RESPIRATORY AND PROTECTIVE EQUIPMENT. SHUT OFF LEAK IF SAFE TO DO SO. VENTILATE AREA; ALLOW TO EVAPORATE. REDUCE VAPORS WITH FOG OR FINE WATER SPRAY.
Neutralizing Agent: NOT APPLICABLE.

Handling

Handling and Storage Precautions: STORE IN A COOL, DRY, WELL-VENTILATED PLACE. KEEP CONTAINER CLOSED WHEN NOT IN USE. KEEP AWAY FROM HEAT, SPARKS, FLAMES AND INCOMPATIBLE MATERIALS.
Other Precautions: USE AN APPROVED EXPLOSION METER WHEN CHECKING CONFINED SPACES.

Exposure Controls

Respiratory Protection: WHERE ENVIRONMENTAL CONTROLS ARE LACKING OR IN ENCLOSED SPACES USE A SELF-CONTAINED BREATHING APPARATUS.
Ventilation: LOCAL VENTILATION AT THE WORKSITE; MECHANICAL (GENERAL) VENTILATION TO MAINTAIN TLV/PEL. USE NON-SPARKING EQUIPMENT.
Protective Gloves: ANY TYPE FOR CYLINDER HANDLING.
Eye Protection: FULL FACE SHIELD
Other Protective Equipment: METATARSAL SHOES; PROTECTIVE CLOTHING.
Work Hygienic Practices: USE REASONABLE CARE IN HANDLING THIS PRODUCT. WASH HANDS AFTER USE AND BEFORE EATING.
Supplemental Safety and Health
VAPOR PRESS: 1603MM HG OR 16.3PSIG.

Chemical Properties

HCC: G2
Boiling Pt: B.P. Text: 31F, -0.5C
Melt/Freeze Pt: M.P/F.P Text: -216F, -138C
Vapor Pres: 16.3 PSIG
Vapor Density: 2.05
Spec Gravity: 0.579
Evaporation Rate & Reference: HIGH (BU AC=1)
Solubility in Water: SLIGHT
Appearance and Odor: COLORLESS, FAINTLY DISAGREEABLE ODOR.
Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid: YES
OXIDIZING AGENTS
Stability Condition to Avoid: SHOCK, FRICTION, HEAT ABOVE 125F/52C, IGNITION SOURCES
Hazardous Decomposition Products: CARBON DIOXIDE, CARBON MONOXIDE.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE AND



LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.