



ECP-MAGENTA TONER PREMIX FOR ECP42

MSDS Number

BBDWL

National Stock Number

6850-00D001109

Product Name

ECP-MAGENTA TONER PREMIX FOR ECP42

Manufacturer

VERSATEC (A XEROX COMPANY)

Product Identification

Product ID:ECP-MAGENTA TONER PREMIX FOR ECP42

MSDS Date:03/14/1990

FSC:6850

NIIN:00D001109

MSDS Number: BBDWL

Responsible Party

VERSATEC (A XEROX COMPANY)

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: EO083

Contractor

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

ISOPARAFFINIC PETROLEUM SOLVENT

CAS: 64742-48-9

Fraction By Weight: >98%

POLYMER

PIGMENT (UNSPECIFIED)

Hazards

LD50 LC50 Mixture:ORAL, LD50 (RAT) = 10 G/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE-INGESTION:LOW TOXICITY. MAY CAUSE GI TRACT IRRITATION. INHALATION:NOT AN IRRITANT.

EYE:IRRITATION. SKIN:REPEATED CONTACT MAY CAUSE IRRITATION.

CHRONIC:DERMATITIS.

Effects of Overexposure:SKIN,EYES:MILD IRRIT; INGEST:DIARRHEA.



INHAL:COUGHING.

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN: WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point Method:TCC
Flash Point:102F/39C TCC
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:CO2, FOAM, DRY CHEM & H2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H2O SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS, CONTAINER MAY BURST IN FIRE.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES, RECOVER FREE LIQUID WITH VERMICULITE, SAWDUST ETC AND SAVE IN A CONTAINER.

Handling

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID STORING/HANDLING NEAR HEAT,STRONG LIGHT,SPARKS,OPEN FLAMES, STRONG OXIDANTS.
Other Precautions:AVOID BREATHING VAPORS AND PROLONGED OR REPEATED SKIN CONTACT

Exposure Controls

Respiratory Protection:NONE
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN Protective Gloves:NEOPRENE,NITRIL
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Work Hygienic Practices:DO NOT EAT, DRINK OR SMOKE WHILE WORKING WITH THIS PRODUCT.
Supplemental Safety and Health
MSDS COVERS DIFF SIZE CONTR SOLD UNDER VERSATEC PART NUMBERS:4803-2, 4T-208-2, 4811-1-1, 4811-32-6

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:320F,160C
Vapor Pres:1MM
Vapor Density:5.0
Spec Gravity:0.77
Evaporation Rate & Reference:0.3 (BU AC=1)
Solubility in Water:IMMISCIBLE
Appearance and Odor:MAGENTA LIQUID, SLIGHT ODOR.
Percent Volatiles by Volume:80-90

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Stability Condition to Avoid:IGNITION SOURCES, HIGH TEMPERATURES
Hazardous Decomposition Products:OXIDES OF CARBON.

Disposal

Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and



assume responsibility for the suitability of this information to their particular situation.