https://msdsreport.com/msds/BBDWM

# **ECP - MAGENTA TONER CONCENTRATE**

# **MSDS Number**

BBDWM

### **National Stock Number**

6850-00D001110

### **Product Name**

ECP - MAGENTA TONER CONCENTRATE

### Manufacturer

VERSATEC (A XEROX COMPANY)

# **Product Identification**

Product ID:ECP - MAGENTA TONER CONCENTRATE MSDS Date:01/01/1987 FSC:6850 NIIN:00D001110 MSDS Number: BBDWM

# **Responsible Party**

VERSATEC (A XEROX COMPANY)

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: EO083

# Contractor

VERSATEC INC (REPLACED BY XES INC, VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

# Ingredients

ISOPARAFFINIC PETROLEUM SOLVENT CAS 64742-48-9 Fraction By Weight: 85% ACGIH TLV: 300 PPM (MFR)

METHACRYLIC COPOLYMER CAS 9011-15-8

Fraction By Weight:

MAGENTA DYE (UNSPECIFIED)

Fraction By Weight:

# Hazards

Effects of Overexposure:SKIN,EYES:MILD IRRIT;INGEST:RESP.DISTRESS & CENTRAL NERVOUS DEPRESSION;INHAL:RESP.ARREST,HEART ARYTH

# First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE



VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

### **Fire Fighting**

Flash Point:102F/39C TCC Lower Limits:0.8 Upper Limits:7.0 Extinguishing Media:CO\*2, FOAM, DRY CHEM & H\*20 FOG. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR. Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS

•

### **Accidental Release**

Spill Release Procedures: REMOVE IGNITION SOURCES, RECOVER FREE LIQUID WITH VERMICULITE, SAWDUST ETC.

### Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED. AVOID STORING/HANDLING NEAR HEAT, STRONG LIGHT, SPARKS OPEN FLAMES, STRONG OXIDANTS. Other Precautions: AVOID BREATHING VAPORS AND PROLONGED OR REPEATED SKIN CONTACT

### **Exposure Controls**

Respiratory Protection:NONE Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN Protective Gloves:NEOPRENE,NITRIL Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE Supplemental Safety and Health MSDS 30SEP86:MSDS COVERS DIFF SIZE CONR SLD UNDER VERSATEC PART NUMBERS:4803-16, 4T-215-16

### **Chemical Properties**

HCC:F4 Boiling Pt:B.P. Text:338F/170C Vapor Pres:1MM Vapor Density:5.0 Spec Gravity:.78 Evaporation Rate & Reference:25-.45 BUAC Solubility in Water:IMMISCIBLE Appearance and Odor:LIQUID, SLIGHT ODOR

#### Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS Stability Condition to Avoid:IGNITION SOURCES, HIGH TEMPERATURES Hazardous Decomposition Products:CO,CO\*2

#### Disposal

Waste Disposal Methods: APPROVED DISPOSAL SITE I/A/W FEDERAL, STATE, LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.