

ECP - CYAN PREMIX TONER

MSDS Number

BBDWY

National Stock Number

6850-00D001120

Product Name

ECP - CYAN PREMIX TONER

Manufacturer

VERSATEC (A XEROX COMPANY)

Product Identification

Product ID:ECP - CYAN PREMIX TONER

MSDS Date:01/01/1987

FSC:6850

NIIN:00D001120

MSDS Number: BBDWY

Responsible Party

VERSATEC (A XEROX COMPANY)

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: EO083

Contractor

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

ISOPARAFFINIC PETROLEUM SOLVENT CAS 64742-48-9

Fraction By Weight: >98%

ACGIH TLV: 300 PPM (MFR)

METHACRYLIC COPOLYMER CAS 9011-15-8

Fraction By Weight:

CYAN DYE (UNSPECIFIED)

Fraction By Weight:

Hazards

Effects of Overexposure:SKIN,EYES:MILD IRRIT;INGEST:RESP.DISTRESS & CENTRAL NERVOUS DEPRESSION;INHAL:RESP.ARREST,HEART ARYTH

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE

VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point:102F/39C TCC

Lower Limits:0.8

Upper Limits:7.0

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS.

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES,RECOVER FREE LIQUID WITH VERMICULITE,SAWDUST,ETC.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED. AVOID STORING/HANDLING NEAR HEAT,STRONG LIGHT,SPARKS,OPEN FLAMES,STRONG OXIDANTS.

Other Precautions:AVOID BREATHING VAPORS AND PROLONGED OR REPEATED SKIN CONTACT.

Exposure Controls

Respiratory Protection:NONE

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN Protective Gloves:NEOPRENE,NITRIL

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE

Supplemental Safety and Health

MSDS 30SEP86:MSDS COVERS DIFF SIZE CONTR SOLD UNDER VERSATEC,PART NUMBERS:4814-32, 4814-2, 4814-1-1, 4814-32-6

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:338F/170C

Vapor Pres:IMM

Vapor Density:5.0

Spec Gravity:.78

Evaporation Rate & Reference:25-.45 BUAC

Solubility in Water:IMMISCIBLE

Appearance and Odor:BLUE LIQUID,SLIGHT ODOR

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS

Stability Condition to Avoid:IGNITION SOURCES,HIGH TEMPERATURES

Hazardous Decomposition Products:CO,CO*2

Disposal

Waste Disposal Methods:APPROVED DISPOSAL SITE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.