

SPECTRUM YELLOW PREMIX TONER

MSDS Number

BBDXF

National Stock Number

6850-00D001125

Product Name

SPECTRUM YELLOW PREMIX TONER

Manufacturer

VERSATEC (A XEROX COMPANY)

Product Identification

Product ID:SPECTRUM YELLOW PREMIX TONER

MSDS Date:01/01/1987

FSC:6850

NIIN:00D001125

MSDS Number: BBDXF

Responsible Party

VERSATEC (A XEROX COMPANY)

2805 BOWERS AVE.

SANTA CLARA , CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: EO083

Contractor

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

ISOPARAFFINIC PETROLEUM SOLVENT CAS 64742-48-9

Fraction By Weight: 90%

ACGIH TLV: 300 PPM (MFR)

METHACRYLIC COPOLYMER CAS 9011-15-8

Fraction By Weight: >5%

YELLOW DYE (UNSPECIFIED)

Fraction By Weight:

Hazards

Effects of Overexposure:SKIN,EYES:MILD IRRIT;INGEST:RESP.DISTRESS &
CENTRAL NERVOUS DEPRESSION;INHAL:RESP.ARREST,HEART ARYTH

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG

DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point:102F/39C TCC
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR.
Unusual Fire/Explosion Hazard:DO NOT STORE WITH STRONG OXIDANTS

Accidental Release

Spill Release Procedures:REMOVE IGNITION SOURCES, RECOVER FREE LIQUID WITH VERMICULITE, SAWDUST, ETC.

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED. AVOID STORING/HANDLING NEAR HEAT,STRONG LIGHT,SPARKS,OPEN FLAMES,STRONG OXIDANTS.
Other Precautions:AVOID BREATHING VAPORS AND PROLONGED OR REPEATED SKIN CONTACT.

Exposure Controls

Respiratory Protection:NONE
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN Protective Gloves:NEOPRENE,NITRIL
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE
Supplemental Safety and Health
MSDS 02OCT86:MSDS COVERS DIFF SIZE CONTR SOLD UNDER VERSATEC PART NUMBER:4832-16-6

Chemical Properties

HCC:F4
Boiling Pt:B.P. Text:338F/170C
Vapor Pres:IMM
Vapor Density:5.0
Spec Gravity:.78
Evaporation Rate & Reference:25-.45 BUAC
Solubility in Water:IMMISCIBLE
Appearance and Odor:YELLOW LIQUID,SLIGHT ODOR

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Stability Condition to Avoid:IGNITION SOURCES,HIGH TEMPERATURES
Hazardous Decomposition Products:CO,CO*2

Disposal

Waste Disposal Methods:APPROVED DISPOSAL SITE I/A/W FEDERAL,STATE,LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.