

SPECTRUM CYAN TONER PREMIX FOR C2552,C2558,C2562,C2568

MSDS Number

BBDXH

National Stock Number

6850-00D001127

Product Name

SPECTRUM CYAN TONER PREMIX FOR C2552,C2558,C2562,C2568

Manufacturer

VERSATEC INC (REPLACED BY XES INC VERSATEC PROD)

Product Identification

Product ID:SPECTRUM CYAN TONER PREMIX FOR C2552,C2558,C2562,C2568

MSDS Date:03/14/1990

FSC:6850

NIIN:00D001127

MSDS Number: BBDXH

Responsible Party

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

2710 WALSH AVE.

SANTA CLARA , CA 95051

US

Emergency Phone: 716-422-2177 (XEROX CORP, NY)

Info Phone: 800-828-6571

Cage: 50804

Contractor

VERSATEC INC (REPLACED BY XES INC,VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

HYDROTREATED HEAVY NAPHTHA/ISOPARAFFINIC HYDROCARBON

CAS: 64742-48-9

Fraction By Weight: 98%

POLYMER

PIGMENTS

OSHA PELNOT ESTABLISHED.

ACGIH TLV: NOT ESTABLISHED.

VOLATILE ORGANIC COMPOUNDS (730 G/L)

RTECS: 9999999VO

OSHA PELNOT RELEVANT

ACGIH TLV: NOT RELEVANT

Hazards

LD50 LC50 Mixture:LD50 (ORAL RAT) IS >10,000 MG/KG.
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE- INGESTION POSES RISK OF SEVERE RESPIRATORY DISTRESS BY ASPIRATION, AS WELL AS CNS DEPRESSION. INTENTIONAL INHALATION MAY RESULT IN ABNORMAL HEART RHYTHMS, RESPIRATORY ARREST, CNS TOXICITY. CONT ACT WITH EYES MAY CAUSE IRRITATION. CONTACT WITH SKIN MAY CAUSE DRYNESS. CHRONIC- UNKNOWN. TARGET ORGANS:LUNGS, CNS.
Effects of Overexposure:EYE, SKIN, RESPIRATORY TRACT IRRITATION, DROWSINESS, DIZZINESS, NAUSEA, VOMITING, HEADACHE
Medical Cond Aggravated by Exposure:NONE WHEN USED AS DESCRIBED BY PRODUCT LITERATURE.

First Aid

First Aid:GET MEDICAL HELP IF SYMPTOMS PERSIST. INHALATION:REMOVE TO FRESH AIR. PROVIDE CPR IF NEEDED. EYES:FLUSH WITH WATER FOR 15 MINUTES, HOLDING EYELIDS OPEN. SKIN:WASH WITH SOAP & WATER. INGESTION:DO NOT INDUCE VOMITING. DILUTE STOMACH CONTENTSWITH SEVERAL GLASSES OF WATER. GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:TCC
Flash Point:102F,39C
Lower Limits:0.8
Upper Limits:7.0
Extinguishing Media:WATER FOG, CO2, FOAM OR DRY CHEMICAL. WATER SPRAY MAY BE USED TO KEEP FIRE EXPOSED CONTAINERS COOL & FLUSH SPILLS AWAY.
Fire Fighting Procedures:USE AIR-SUPPLIED BREATHING EQUIPMENT FOR ENCLOSED AREAS. COOL EXPOSED CONTAINERS WITH WATER SPRAY. AVOID BREATHING VAPOR OR FUMES.
Unusual Fire/Explosion Hazard:VAPOR IS HEAVIER THAN AIR AND MAY TRAVEL CONSIDERABLE DISTANCE TO A SOURCE OF IGNITION AND FLASH BACK. CONTAINERS MAY RUPTURE DUE TO VAPOR PRESSURE BUILDUP.

Accidental Release

Spill Release Procedures:WEAR PROTECTIVE EQUIPMENT. ELIMINATE SOURCES OF IGNITION. VENTILATE AREA. CONTAIN SPILL. PICK UP SPILL WITH NON-FLAMMABLE ABSORBENT MATERIAL/USE PUMP. PLACE IN CONTAINER FOR DISPOSAL. PREVENT LIQUID FROM ENTERING SEWERS, WATERWAYS OR LOW AREAS.
Neutralizing Agent:NOT RELEVANT

Handling

Handling and Storage Precautions:KEEP CONTAINER CLOSED. AVOID HANDLING NEAR HEAT, SPARKS, STRONG LIGHT, OPEN FLAMES, STRONG OXIDANTS.
Other Precautions:DO NOT BREATHE VAPORS. AVOID CONTACT WITH EYES. AVOID PROLONGED OR REPEATED SKIN CONTACT. FOR INDUSTRIAL USE ONLY. WASH THOROUGHLY AFTER HANDLING. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:NONE WHEN USED AS INTENDED WITH VERSATEC (XEROX) PRODUCTS.
Ventilation:ADEQUATE
Protective Gloves:NEOPRENE/NITRILE FOR PROLONGED CONTACT
Eye Protection:NONE WHEN USED AS INTENDED.
Other Protective Equipment:EYE WASH STATION.
Work Hygienic Practices:WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING OR DRINKING. DO NOT WEAR CONTAMINATED CLOTHING OR FOOTWEAR.
Supplemental Safety and Health
MSDS 2058. MFR SELL PRODUCT IN VARIOUS SIZES COVERED BY NUMBERS 4834-16-6,4844-16-3,4854-16-6.

Chemical Properties

HCC:F4
NRC/State Lic Num:NOT RELEVANT
Boiling Pt:B.P. Text:320F - 356F
Vapor Pres:1 @ 68F
Vapor Density:5.0
Spec Gravity:0.77
Evaporation Rate & Reference:0.3 (N-BUTYL ACETATE=1)
Solubility in Water:IMMISCIBLE
Appearance and Odor:MAGNETA LIQUID - SLIGHT ODOR
Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS SUCH AS LIQUID CHLORINE, CONCENTRATED OXYGEN,
SODIUM OR CALCIUM HYPOCHLORITE
Stability Condition to Avoid:HEAT, SPARKS, FLAMES, HOT SURFACES AND
OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:FUMES, SMOKE AND CARBON MONOXIDE IN
THE CASE OF INCOMPLETE COMBUSTION.

Disposal

Waste Disposal Methods:THE WASTE TONER MAY BE CLASSIFIED AS AN
IGNITABLE HAZARDOUS WASTE UNDER FEDERAL AND/OR STATE REGULATIONS
AND SHOULD BE DISPOSED AT AN APPROVED DISPOSAL SITE OR FACILITY IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.