HYDRO-SEAL, HEAVY DUTY COLD PART CLNR, HS-8K

MSDS Number

BBDXW

National Stock Number

5970-00D001139

Product Name

HYDRO-SEAL, HEAVY DUTY COLD PART CLNR, HS-8K

Manufacturer

RADIATOR SPECIALTY CO

Product Identification

Product ID: HYDRO-SEAL, HEAVY DUTY COLD PART CLNR, HS-8K

MSDS Date: 01/01/1987

FSC:5970

NIIN:00D001139

MSDS Number: BBDXW

Responsible Party

RADIATOR SPECIALTY CO.

1400 W. INDEPENDENCE BLVD.

CHARLOTTE, NC 28208

Emergency Phone: 704-377-6555

Info Phone: 704-377-6555

Cage: 77628

Contractor

RADIATOR SPECIALTY COMPANY

34689

US

CHARLOTTE, NC 28208

704-377-6555/303-623-5716

Cage: 77628

Ingredients

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight: 1.2%

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

PHENOL

CAS: 108-95-2

RTECS: SJ3325000

Fraction By Weight: 3.4%



OSHA PELS, 5 PPM

ACGIH TLV: S, 5 PPM; 8990 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

CRESOL, ALL ISOMERS (CRESYLIC ACID) (SARA III)

CAS: 1319-77-3 RTECS: GO5950000

Fraction By Weight: 13.3%

OSHA PELS, 5 PPM

ACGIH TLV: S, 5 PPM; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS: 127-18-4 RTECS: KX3850000

Fraction By Weight: 8.1%

OSHA PEL100 PPM

ACGIH TLV: 25PPM/100,A3 STEL;94

EPA Report Quantity: 100 LBS DOT Report Quantity: 100 LBS

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2 RTECS: PA8050000

Fraction By Weight: 34.6% OSHA PEL500 PPM/C,1000; Z2 ACGIH TLV: 50 PPM, A2; 9192 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: SEVERE IRRITANT TO EYES.SKIN; DIZZINESS, NARCOSIS, CORROSIVE TO MOUTH, THROAT, DIGESTIVE SYS, MAY BE FATAL

First Aid

First Aid:EYE:CONSULT PHYSICIAN IMMEDIATELY; SKIN: WASH WITH SOAP & WATER, IN CASE OF SKIN BURNS, CONSULT PHYSICIAN; INH: REMOVE TO FRESH AIR; ING: DO NOT INDUCE VOMITING, CONSULT PHYSICIAN IMMEDIATELY.

Fire Fighting

Extinguishing Media: NONE

Fire Fighting Procedures: WEAR CHEMICAL PROTECTIVE SUIT WITH SELF CONTD

BRTHG APP.

Unusual Fire/Explosion Hazard: PHENOLIC & CHLORINATED FUMES.

Accidental Release



Spill Release Procedures: OBSERVING HEALTH HAZARDS, VENTILATE AREA. WEAR PROTECTIVE GEAR. CONFINE SPILL & SOAK UP WITH ABSORBENT CLAY. TRANSFER TO WASTE DRUM WITH CLOSURE.

Handling

Handling and Storage Precautions: STORE IN COOL PLACE, KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection: IF TLV IS EXCEEDED, WEAR RESPIRATORY WITH ORGANIC VAPOR CARTRIDGE.

Ventilation: ADEQUATE VENTILATION & LOCAL EXHAUST.

Protective Gloves: SOLVENT-RESIST. Eye Protection: CHEM SPLASH GOGGLES Other Protective Equipment: APRON.

Supplemental Safety and Health

MSDS DATED 4-86. SAME MSDS USED FOR P/N: HS-3K,-5K,-5LB,-7,-7K-8, & -8K. "OTHER INGRED": SODIUM DICHROMATE DIHYDRATE(0.2%).

Chemical Properties

HCC:T4

Boiling Pt:B.P. Text:100F/38C

Spec Gravity:1.17

Solubility in Water: EMULSIFIABL

Appearance and Odor: DARK AMBER LIQ W/25% FLOATING WATER SEAL. PHENOL OD

Percent Volatiles by Volume:72

Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS & OXIDING AGENTS.

Stability Condition to Avoid: DO NOT USE IN CONFINED AREAS WITHOUT VENTILATION.

Hazardous Decomposition Products: IN CONTACT HOT METAL SURFACE: HYDROGEN CHLORIDE, PHOSGENE.

Disposal

Waste Disposal Methods: KEEP IN COVERED DRUMS, PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.