

NSPA-16;NEVER-SEEZ PENETRATING OIL

MSDS Number

BBDXY

National Stock Number

6850-00D001141

Product Name

NSPA-16;NEVER-SEEZ PENETRATING OIL

Manufacturer

BOSTIK INDUSTRIAL DIV EMHART FASTENING SYSTEMS GP

Product Identification

Product ID:NSPA-16;NEVER-SEEZ PENETRATING OIL

MSDS Date:01/01/1987

FSC:6850

NIIN:00D001141

MSDS Number: BBDXY

Responsible Party

BOSTIK INDUSTRIAL DIV.,EMHART FASTENING SYSTEMS GP

BOSTON ST

MIDDLETON , MA 01949

US

Cage: EO086

Contractor

USM CORP SUB OF EMHART INDUSTRIES INC BOSTIK DIV

MIDDLETON, MA 01949

US

508-777-0100

Cage: 70707

Ingredients

PERCHLOROETHYLENE (TETRACHLOROETHYLENE) (SARA III)

CAS: 127-18-4

RTECS: KX3850000

Fraction By Weight: 58.0%

OSHA PEL100 PPM

ACGIH TLV: 25PPM/100,A3 STEL;94

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 22.0%

OSHA PEL350 PPM/450 STEL

ACGIH TLV: 350 PPM/450STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

UNIDENTIFIED COMPONENT

ACGIH TLV: NOT SPECIFIED

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: VL8047000

Fraction By Weight: 5.0%

OSHA PEL100 PPM

Hazards

Effects of Overexposure:IRRITATION OF EYES,NOSE AND THROAT,DRYING OF SKIN,WEAKNESS,CONFUSION,HEAD,NAUSEA;HIGH EXP-NARCOSIS.

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point:NONE

Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.

Unusual Fire/Explosion Hazard:AVOID TEMP >120F;CONTAINERS MAY BURST.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;TEMP SHOULD BE BELOW 120F.KEEP CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH SKIN,EYES AND CLOTHES.DO NOT INHALE VAPOR/MIST;WASH THOROUGHLY AFTER EACH USE.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORG VAPORS OR SCBA IF >TLV.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION

Supplemental Safety and Health

MSDS DATED:04/17/86.

Chemical Properties

HCC:T4

Boiling Pt:B.P. Text:165-280F

Vapor Pres:140

Vapor Density:5.4

Spec Gravity:1.46

Evaporation Rate & Reference:7.0 (ETYL ETER=1)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:A WATER WHITE TO WHITE LIQUID,SOLVENT ODOR.
Percent Volatiles by Volume:88

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZING AGENTS,WATER
Stability Condition to Avoid:TEMP ABOVE 120F
Hazardous Decomposition Products:COMBUSTION:CO,CO*2,HCL, OR TOXIC FUMES

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH
LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.