

F-927 PETROLEUM LUBRICATING GREASE

MSDS Number

BBDYB

National Stock Number

9150-00D001144

Product Name

F-927 PETROLEUM LUBRICATING GREASE

Manufacturer

NONFLUID OIL CORP

Product Identification

Product ID:F-927 PETROLEUM LUBRICATING GREASE

MSDS Date:01/01/1987

FSC:9150

NIIN:00D001144

MSDS Number: BBDYB

Responsible Party

NONFLUID OIL CORPORATION

Emergency Phone: (201)344-3451

Cage: 76736

Contractor

NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

NEWARK, NJ 07105-3009

US

201-344-3451/800-424-9300(CHEMTREC)

Cage: 76736

Ingredients

PETROLEUM HYDROCARBONS

ACGIH TLV: N/R(NOT MISTED)

ADDITIVES

ACGIH TLV: N/R(NOT MISTED)

Hazards

Effects of Overexposure:SKIN:MILD IRR,DEFAT;INH:MUC.MEMBR.IRR.

First Aid

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.

INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED

CLOTHING;ING:ADMINISTER VOLUMES OF WATER OR MILK AND SEEK MEDICAL AID.

Fire Fighting

Flash Point:400F,204C,COC

Lower Limits:1

Upper Limits:6

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.

Fire Fighting Procedures:USE WTR SPRAY TO KEEP CONT. COOL & TO FLUSH SPILLS AWAY.

Unusual Fire/Explosion Hazard:SLIGHT WHEN EXPOSED TO EXCESSIVE HEAT OR

FLAME.CAN REACT W.OXIDIZING AGENTS.DO NOT STORE W.OXIDANTS.

Accidental Release

Spill Release Procedures:STOP FLOW.ELIMINATE IGN.SOURCES. RECOVER FREE PRODUCT. ADD ABSORBANT TO SPILL AREA. MOP UP OR SCRAPE UP AND PLACE IN SUITABLE DISPOSAL CONTAINERS.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICTION. KEEP CONTAINERS CLOSED.

Other Precautions:DO NOT STORE OR MIX WITH OXIDIZING MATERIALS-AVOID PROLONGED/REPEATED CONTACT W.SKIN.AVOID CONTACT W.EYES AND INHAL.OF FUMES,VAPORS,MIST.DO NOT WEAR CONTAM.CLOTHING.REMOVE&LAUNDER BEFORE REUSE

Exposure Controls

Respiratory Protection:USUALLY NOT REQ'D. NIOSH APPVD RESP. IF FUMING OR MISTING.

Ventilation:USUALLY NOT REQ'D. LOCAL EXH&MECHANICAL VENT ONLY IF MISTING

Protective Gloves:RUBBER/PLASTIC

Eye Protection:GOGGLES IF MISTING

Other Protective Equipment:USUALLY NOT REQD-PROTECTIVE CLOTH IF SPLASHING OR MISTING.

Supplemental Safety and Health

MSDS UNDATED/

Chemical Properties

HCC:V6

Boiling Pt:B.P. Text:>600F,>316C

Vapor Pres:Vapor Density:>10

Spec Gravity:0.9

Evaporation Rate & Reference:Solubility in Water:DISPERSIBLE

Appearance and Odor:TAN/AMBER SEMI-SOLID GREASE-SLIGHT PETROLEUM ODOR.

Percent Volatiles by Volume:NEGL

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDANTS,CONC.OXYGEN,LIQ.CHLORINE,PEROXIDES.

Stability Condition to Avoid:EXCESSIVE HEAT AND OPEN FLAME.

Hazardous Decomposition Products:OXYGENATES;OXIDES OF COR CA;TRACES OF OXIDES OF NA,ZN;CO

Disposal

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.