

AGS TOPAZ BRONZE ACRYLIC LAC

MSDS Number

BBDYV

National Stock Number

8010-00D001170

Product Name

AGS TOPAZ BRONZE ACRYLIC LAC

Manufacturer

AMES SUPPLY CO

Product Identification

Product ID: AGS TOPAZ BRONZE ACRYLIC LAC

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00D001170

MSDS Number: BBDYV

Responsible Party

AMES SUPPLY CO.

Emergency Phone: (312)964-2440

Cage: EO069

Contractor

AMES SUPPLY CO.

Cage: EO069

Ingredients

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 5 - 10%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight:

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500 STEL; 9192

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 20%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:ANESTH,IRR TO SKIN/UPPR RESP.SYS; LIGHT HEAD,STAGGRNG GAIT,GIDD,NAUSEA;HARMFUL/FATAL IF SWALLOWED.

First Aid

First Aid:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. SKIN:WASH WITH SOAP & WATER. EYES:FLUSH WITH WATER 15 MIN. KEEP WARM AND QUIET. ING:DO NOT INDUCE VOMIT,CALL PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point:Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WTR INEFF-USE WTR TO KEEP CONT.COOL-USE SHIELD FOR PROTECTN.

Unusual Fire/Explosion Hazard:DO NOT SPRAY NEAR OPEN FLAME-KEEP AT ROOM TEMP,AS EXPOSURE TO SUNLIGHT,OTHER HEAT,CAUSES BURSTING.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION,VENTILATE,AVOID BREATHING VAPORS AND REMOVE WITH INERT ABSORBENT.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENT,LOW FIRE RISK AREA.PROTECT CONT.FROM PHYS.DAMAGE.DO NOT STORE ABOVE 120F.

Other Precautions:KEEP AT ROOM TEMP. AS EXPOSURE TO DIRECT SUNLIGHT MAY CAUSE BURSTING.

Exposure Controls

Respiratory Protection:NIOSH APPVD RESP.IF TLV IS EXCEEDED.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES

Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.

Supplemental Safety and Health

MSDS DATED 01-03-86/OTHER

INGREDIENTS:ETHYL-ETHOXYPROPIONATE20%;PROPANE 15%/B.P.<-18C(PROPELLANT)/F.P.<-7C,TOC,PROPELLANT/

Chemical Properties

HCC:V3

Boiling Pt:B.P. Text:Vapor Density:>1

Evaporation Rate & Reference:>1(ETHER=1),PROPEL

Appearance and Odor:NOT NOTED BY MFR

Percent Volatiles by Volume:91

Stability

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:AVOID TEMPS ABOVE 120F;AVOID FIRE,OPEN
FLAME.

Hazardous Decomposition Products:CO,CO*2,HCL

Disposal

Waste Disposal Methods:DO NOT PUNCTURE OR INCINERATE CONTAINER,GIVE TO
DISPOSAL SERVICE-DISPOSE OF IAW LOCAL,STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.