GEAR LUBE 75W90(GL-5);AGR

MSDS Number

BBDZB

National Stock Number

9150-00D001175

Product Name

GEAR LUBE 75W90(GL-5);AGR

Manufacturer

AMSOIL INC

Product Identification

Product ID:GEAR LUBE 75W90(GL-5);AGR
MSDS Date:01/01/1987
FSC:9150
NIIN:00D001175
MSDS Number: BBDZB

Responsible Party

AMSOIL INC.

Emergency Phone: 715-392-7101

Cage: EO090

Contractor

AMSOIL INC.

SUPERIOR, WI 54880

US

715-392-7101

Cage: EO090

Ingredients

SYNTHETIC OIL (TLV PER MSDS AS OIL MIST=5MG/CUM)

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:EYES:SLIGHT IRRITATION;SKIN:IRRITATION ON PROLONGED CONTACT;INHAL:RESP TRACT IRRITATION;ING:G.I.IRRI

First Aid

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

Fire Fighting

Flash Point:392F/200C (D-92)
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:NONE INDICATED

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AREA.STORE BELOW 45C.KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP OUT OF REACH OF CHILDREN.
Other Precautions:AVOID CONTACT WITH EYES & SKIN;DO NOT BREATHE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF > TLV.
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEM GOGGLES
Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.
Supplemental Safety and Health
MSDS DATED:10/8/86.

Chemical Properties

HCC:V6
Spec Gravity:0.872
Evaporation Rate & Reference:Solubility in Water:NEGLIGIBLE
Appearance and Odor:LIGHT AMBER MOBILE LIQUID,ODOR GEAR LUBRICANTS.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Stability Condition to Avoid:EXTREME HEAT,OPEN FLAMES
Hazardous Decomposition Products:OXIDES OF CARBON,S,N,P,B.FUMES MAY CONTAIN H*2S & HCL

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.