

RNICR-C-1 WELDING ROD

MSDS Number

BBDZM

National Stock Number

3439-00D001190

Product Name

RNICR-C-1 WELDING ROD

Manufacturer

NATIONAL WELDING ALLOYS INC

Product Identification

Product ID:RNICR-C-1 WELDING ROD

MSDS Date:01/01/1987

FSC:3439

NIIN:00D001190

MSDS Number: BBDZM

Responsible Party

NATIONAL WELDING ALLOYS,INC.

Emergency Phone: (412)781-4255

Cage: 0ACE2

Contractor

NATIONAL WELDING ALLOYS INC

PITTSBURGH, PA 15215-2624

US

412-781-4255

Cage: 0ACE2

Ingredients

NICKEL (SARA III)

CAS: 7440-02-0

RTECS: QR5950000

Fraction By Weight: 71.3%

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

CHROMIUM (SARA III)

CAS: 7440-47-3

RTECS: GB4200000

Fraction By Weight: 15.0%

OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

IRON,CAS#7439-89-6,3.5-5.5%

CAS: 7439-89-6

RTECS: NO4565500

Fraction By Weight: 4.5%

ACGIH TLV: 5MG/CUM

SILICON

CAS: 7440-21-3

RTECS: VW0400000

Fraction By Weight: 4.5%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

BORON,CAS#7440-42-8,2.5-4.5%

CAS: 7440-42-8

RTECS: ED7350000

Fraction By Weight: 3.5%

Hazards

Effects of Overexposure:METALLIC TASTE,NAUSEA,TIGHTNESS OF CHEST,FEVER,DIZZINESS.EYE,NOSE,THROAT DRYNESS AND IRRITATION.

First Aid

First Aid:REMOVE FROM EXPOSURE AND OBTAIN PROMPT MEDICAL ATTENTION.IF UNCONSCIOUS,GIVE OXYGEN.IF NOT BREATHING GIVE CPR.EMPLOY FIRST AID TECHNIQUES RECOMMENDED BY AMERICAN RED CROSS.

Fire Fighting

Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Unusual Fire/Explosion Hazard:WELDING ARC AND SPARKS CAN IGNITE COMBUSTIBLE PRODUCTS.

Accidental Release

Spill Release Procedures:CLEAN UP ANY GRINDING DUST OR WASTE RESIDUE AND PLACE IN SUITABLE DOT APPROVED DISPOSAL CONTAINER.

Handling

Other Precautions:TRAIN WELDER TO KEEP HIS HEAD OUT OF THE FUMES,MONITOR AIR TO ENSURE ACCEPTABLE EXPOSURES.AVOID ELECTRICAL SHOCK BY MAINTAINING DRY WORK AREA.

Exposure Controls

Respiratory Protection:FUME RESP.OR AIR SUPPLIED RESP.IN CONFINED SPACES.
Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.
Protective Gloves:WELDER'S GLOVES
Eye Protection:FACE SHLD W/FILTER LENS.
Other Protective Equipment:SUBST.DK.CLOTH,ARM PROTECTOR,APRON,HAT,SHOULDER PROTECTION.
Supplemental Safety and Health
MSDS UNDATED/OTHER INGRED:COBALT 1.0% MAX,CARCINOGENIC IN EXPERIMENTAL ANIMALS;CARBON,0.5-1.0%/

Chemical Properties

HCC:N1

Appearance and Odor:WELDING ROD

Stability

Stability Indicator/Materials to Avoid: YES
Hazardous Decomposition Products: FUMES OF METALS AND METAL
OXIDES, CO, NO*2, O*3.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.