

## **803 MINERAL SPIRITS**

### **MSDS Number**

BBDZN

### **National Stock Number**

6810-00D001191

### **Product Name**

803 MINERAL SPIRITS

### **Manufacturer**

SUNNYSIDE CORP

### **Product Identification**

Product ID:803 MINERAL SPIRITS

MSDS Date:01/01/1987

FSC:6810

NIIN:00D001191

MSDS Number: BBDZN

### **Responsible Party**

SUNNYSIDE CORPORATION

225 CARPENTER AVE

WHEELING , IL 60090-6009

US

Cage: 9J570

### **Contractor**

SUNNYSIDE CORP

WHEELING, IL 60090-6009

US

847-541-5700

Cage: 9J570

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 100%

OSHA PEL100 PPM

### **Hazards**

Effects of Overexposure:EYE,SKN:POSS IRRT. INHL:URT  
IRRIT,DIZZ,HEADACHE,DEPRESS,CONVUL,LOSS  
CONSC.INGEST:IRRIT,NAUS,DIARR.

### **First Aid**

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG  
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE  
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

### **Fire Fighting**

Flash Point:102F/39C TCC

Lower Limits:0.9

Extinguishing Media:CO\*2,FOAM,DRY CHEMICAL, WATER SPRAY.  
Fire Fighting Procedures:WEAR SCBA PP MODE.DO NOT USE WATER JET.COOL  
EXP CONTAINERS.  
Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX W/STRONG OXIDANTS

## Accidental Release

Spill Release Procedures:EVACUATE AREA, REMOVE IGNITION SOURCES,WEAR  
SCBA PP MODE,CONFINE SPILL, STOP LEAK.COLLECT SPILL W/NON-SPARK  
SCOOP OR ABSORBENT, PLACE IN CLOSABLE CONTAINER. DO NOT FLUSH TO  
SEWER OR WATERWAY.

## Handling

Handling and Storage Precautions:STORE IN COOL, DRY AREA,AWAY FROM HEAT  
& IGNITION SOURCES. KEEP CONTAINERS CLOSED. GROUND CONTAINERS  
DURING TRANSFER.

Other Precautions:AVOID EYE-SKN CONTACT. DO NOT INHAL OR INGEST. USE  
CAUTION W/EMPTY CONTAINERS-MAY CONTAIN FLAMMABLE RESIDUE. DO NOT  
ATTEMPT CLEANUP OF EMPTY CONTR BUT RETURN TO MFR. OR,LANDFILL PER  
REGS.

## Exposure Controls

Respiratory Protection:USE CCROV OR SCBA PP MODE AS REQD.  
Ventilation:LOCAL VENTILATION.  
Protective Gloves:RUBBER,NEOPRENE  
Eye Protection:SAFETY GOGGLE.  
Other Protective Equipment:IMPERVIOUS CLOTHING & BOOTS.  
Supplemental Safety and Health  
MSDS NON-STD DATED 15JAN86.

## Chemical Properties

HCC:F4  
Boiling Pt:B.P. Text:315-395F  
Vapor Density:>1.0  
Spec Gravity:0.79  
Evaporation Rate & Reference:Solubility in Water:NEG.  
Appearance and Odor:WATER-WHITE LIQUID, PETROLEUM ODOR.  
Percent Volatiles by Volume:100

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Stability Condition to Avoid:EXCESS HEAT, IGNITION SOURCES.  
Hazardous Decomposition Products:CARBON OXIDES

## Disposal

Waste Disposal Methods:RECLAIM OR INCINERATE IAW ALL LAWS & REGS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.