

W7000 ACRYSHEEN ACRYLIC, W7000

MSDS Number

BZZYC

National Stock Number

8010-00N016668

Product Name

W7000 ACRYSHEEN ACRYLIC, W7000

Manufacturer

EVR GARD COATINGS CO

Product Identification

Product ID:W7000 ACRYSHEEN ACRYLIC, W7000 MSDS Date:06/01/1992

FSC:8010 NIIN:00N016668 MSDS Number: BZZYC

Responsible Party

EVR-GARD COATINGS CO

16400 GARFIELD AVE

PARAMOUNT, CA 90723

US

Emergency Phone: 310-531-0131

Info Phone: 310-531-0131

Cage: 5G582

Contractor

EVR-GARD COATINGS CO

PARAMOUNT, CA 90723

US

310-531-0131 Cage: 5G582

Ingredients

ETHYLENE GLYCOL; (502 ETHYLENE GLYCOL) (SARA 313) (CERCLA)

CAS: 107-21-1 RTECS: KW2975000

OSHA PELN/K

ACGIH TLV: C 50 PPM, VAPOR EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

242 G/L (COATING) RTECS: 9999999VO

OSHA PELN/K ACGIH TLV: N/K

Hazards



LD50 LC50 Mixture: NONE SPECIFIED BY MANUFACTURER. Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE: INHALATION: MAY CAUSE HEADACHE AND NAUSEA, DIZZINESS. SKIN/EYES/SKIN ABSORPTION: PRIMARILY AN IRRITANT. REDNESS/RASH ON SKIN. INGESTION: NAUSEA, DIZZINESS,

HEADACHES. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

Explanation of Carcinogenicity: NOT RELEVANT. Effects of Overexposure: SEE HEALTH HAZARDS.

Medical Cond Aggravated by Exposure:PROLONGED CONTACT WITH MATERIAL MAY

CAUSE DERMATITIS.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH CLEAN WATER FOR AT LEAST 15 MINUTES. SKIN: REMOVE SATURARED CLOTHING AND WASH SKIN WITH SOAPY WATER THOROUGHLY. INGESTION: IF SWALLOWED, INDUCE VOMITI NG WITH 1 OZ OF SYRUP OF IPECAC FOLLOWED IN 5 MINUTES WITH A GLASS OF WATER. CALL MD.

Fire Fighting

Lower Limits: 0.6%

Extinguishing Media: USE FOAM, ALCOHOL FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: WEAR NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE EQUIPMENT . THIS IS A WATER-BASED PRODUCT. WILL NOT SUPPORT COMBUSTION.

Unusual Fire/Explosion Hazard: NONE.

Accidental Release

Spill Release Procedures: ABSORB SPILL WITH ANY ABSORBENT MATERIAL (SAWDUST, SAND, CLAYS, ETC) AND FLUSH SPILL AREA WITH LOTS OF WATER

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Handling

Handling and Storage Precautions: THIS PRODUCT IS STABLE UNDER NORMAL USE AND STORAGE CONDITIONS. KEEP OUT OF REACH OF CHILDREN. KEEP FROM FREEZING.

Other Precautions: KEEP FROM FREEZING. DO NOT TAKE INTERNALLY.

Exposure Controls

Respiratory Protection: THE USE OF NIOSH/MSHA APPROVED MASKS DURING APPLICATIONS TO AVOID EXCESSIVE INHALATION OF VAPORS IS HIGHLY RECOMMENDED. OPEN WINDOWS AND DOORS OR USE OTHER MEANS TO INSURE FRESH AIR ENTRY DURING APPLI CATION AND DRYING.

Ventilation: PROVIDE ADEQ VENT AT ALL TIMES DURING HNDLG & APPLICATION OF THIS PROD. INSURE ADEQ SUPPLY OF FRESH AIR AT ALL TIMES.

Protective Gloves: BUNA N.

Eye Protection: ANSI APPRVD CHEM WORKERS GOGGS .

Other Protective Equipment: EMERGENCY EYEWASH & DELUGE SHOWER MEETING ANSI DESIGN CRITERIA .

Work Hygienic Practices: OBSERVE STANDARD HYGIENE PRACTICES WHEN HANDLING THIS PRODUCT.

Supplemental Safety and Health

NONE SPECIFIED BY MANUFACTURER.

Chemical Properties

Vapor Pres:SEE ING 1 Vapor Density:HVR/AIR Spec Gravity:1.3 (H*2O=1)

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: DILUTABLE

Appearance and Odor: WHITE PAINT AND COLORS, WITH SLIGHT AMMONIA ODOR

Stability

Stability Indicator/Materials to Avoid:YES



STRONG ACIDS AND ALKALIS AND MATERIALS THAT REACT WITH WATER. Stability Condition to Avoid: DO NOT STORE IN HIGH TEMPERATURE AREAS. Hazardous Decomposition Products: NONE.

Disposal

Waste Disposal Methods: PLACE ALL HAZARDOUS WASTES, INCLUDING ABSORBENTS USED FOR SPILLS, IN 55-GAL METAL DRUMS AND DISPOSE IN APPROVED DUMPSITE IN ACCORDANCE WITH PRESCRIBED FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.