

B-2-107 STICKING CEMENT

MSDS Number

BBFBW

National Stock Number

5970-00D001235

Product Name

B-2-107 STICKING CEMENT

Manufacturer

WESTINGHOUSE DIV

Product Identification

Product ID:B-2-107 STICKING CEMENT

MSDS Date:01/01/1987

FSC:5970

NIIN:00D001235

MSDS Number: BBFBW

Responsible Party

WESTINGHOUSE DIVISION

INSULATING MATERIALS DIVISION PLANT

MANOR , PA 15665

US

Cage: EO099

Contractor

WESTINGHOUSE ELECTRIC CORP

MANOR, PA 15665

US

412-864-8200

Cage: 11927

Ingredients

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 15%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

ETHYL ALCOHOL (ETHANOL)

CAS: 64-17-5

RTECS: KQ6300000

Fraction By Weight: 15%

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM; 9192

Hazards

Effects of Overexposure:EYE & RESP TRACT IRRIT.

ATAXIA,PROSTRATION,NAR,COMA,RESP
ARREST,DEATH,NAU,VOMIT,HEMOR,DIARRHEA.

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH
W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT
UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point:55F,12.7C TCC
Lower Limits:2.0
Upper Limits:19.0
Extinguishing Media:CO*2,ALCOHOL FOAM
Fire Fighting Procedures:WEAR SCBA. DILUTE W/WATER
Unusual Fire/Explosion Hazard:FLAMMABLE VAPORS MAY SPREAD.

Accidental Release

Spill Release Procedures:AVOID CONTACT W/LIQUID OR SOLID. AVOID BRTHNG
VAPORS. USE PROTECT EQUIPMT. ABSORB LIQUID ON ABSORBENT MATL. DIKE
FOR LARGE SPILL. PUMP LIQUID TO SALVAGE DRUM.

Handling

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINER.
KEEP IN COOL WELL-VENTILATED AREA WHERE SOURCES OF IGNITION ARE
EXCLUDED.
Other Precautions:DO NOT REUSE "EMPTY" CONTAINERS W/O COMMERCIAL
CLEANING.

Exposure Controls

Respiratory Protection:NIOSH APPROVED SELF-CONTAINED BREATHING
APPARATUS.
Ventilation:MECHANICAL (GEN) AND/OR LOCAL EXHAUST VENTILATION.
Protective Gloves:RUBBER/VINYL
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:IMPERVIOUS CLOTHING.
Supplemental Safety and Health
MSDS DATED 12-26-85

Chemical Properties

HCC:F3
Boiling Pt:B.P. Text:176F,80C
Vapor Pres:34
Vapor Density:1.9
Spec Gravity:0.894
Evaporation Rate & Reference:7.7 (ISOPROPANOL=1
Solubility in Water:MODERATE
Appearance and Odor:TAN LIQUID, ALCOHOLIC ODOR
Percent Volatiles by Volume:32

Stability

Stability Indicator/Materials to Avoid:YES
ANHYDRIDE,ISOCYANATE,MONOMER & ORGANOMETALLIC COMPOUNDS.
Stability Condition to Avoid:HEAT,SPARKS & OPEN FLAME
Hazardous Decomposition Products:CO & CO*2 & TOXIC VAPORS

Disposal

Waste Disposal Methods:INCINERATION I/A/W ALL LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.