

CE PROCESS BLACK PREMIX TONER

MSDS Number

BBFCP

National Stock Number

6850-00D001255

Product Name

CE PROCESS BLACK PREMIX TONER

Manufacturer

VERSATEC (A XEROX COMPANY)

Product Identification

Product ID:CE PROCESS BLACK PREMIX TONER MSDS Date:01/01/1987 FSC:6850 NIIN:00D001255 MSDS Number: BBFCP

Responsible Party

VERSATEC (A XEROX COMPANY)

2805 BOWERS AVE.

SANTA CLARA, CA 95051

Emergency Phone: 716-422-2177

Info Phone: 800-828-6571

Cage: E0083

Contractor

VERSATEC INC (REPLACED BY XES INC, VERSATEC PROD.)

SANTA CLARA, CA 95051-0905

US

716-422-2177 (XEROX CORP, NY)

Cage: 50804

Ingredients

ISOPARAFFINIC PETROLEUM SOLVENT CAS 64742-48-9

Fraction By Weight: >90% ACGIH TLV: 300 PPM (MFR)

METHACRYLATE COPOLYMER CAS 9011-15-8

CARBON BLACK
CAS: 1333-86-4
RTECS: FF5800000
Fraction By Weight:

OSHA PEL3.5 MG/M3

Fraction By Weight:

ACGIH TLV: 3.5 MG/M3; 9192

Hazards

Effects of Overexposure:SKIN,EYES:MILD IRRIT;INGEST:RESP.DISTRESS &



CENTRAL NERVOUS DEPRESSION; INHAL: RESP. ARREST, HEART ARYTH

First Aid

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

Fire Fighting

Flash Point Method:TCC Flash Point:=38.9C, 102.F

Lower Limits: 0.8 Upper Limits: 7.0

Extinguishing Media:CO*2, FOAM, DRY CHEM & H*20 FOG.

Fire Fighting Procedures: WEAR SELF-CNTD BRTHG, APP H*20 SPRAY TO COOL

CONTR.

Unusual Fire/Explosion Hazard: DO NOT STORE WITH STRONG OXIDANTS

Accidental Release

Spill Release Procedures: REMOVE IGNITION SOURCES, RECOVER FREE LIQUID WITH VERMICULITE, SAWDUST, ETC.

Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED. AVOID STORING/HANDLING NEAR HEAT, STRONG LIGHT, SPARKS, OPEN FLAMES, STRONG OXIDANTS.

Other Precautions: AVOID BREATHING VAPORS AND PROLONGED OR REPEATED SKIN CONTACT.

Exposure Controls

Respiratory Protection: NONE

Ventilation: PROVIDE MECHAN(GEN/LOCAL EXHAUST) VENT TO MAINTN Protective Gloves: NEOPRENE, NITRIL

Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE Supplemental Safety and Health

MSDS 23DEC85:MSDS COVERS DIFF SIZE CONTR SOLD UNDER VERSATEC PART

NUMBERS:4821-1-1, 4821-32-6

Chemical Properties

HCC:F4

Boiling Pt:=170.C, 338.F

Vapor Pres:IMM Vapor Density:5.0 Spec Gravity:.78

Evaporation Rate & Reference: 25-.45 BUAC

Solubility in Water: IMMISCIBLE

Appearance and Odor: BLACK LIQUID, SLIGHT ODOR

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS

Stability Condition to Avoid: IGNITION SOURCES, HIGH TEMPERATURES

Hazardous Decomposition Products:CO,CO*2

Disposal

Waste Disposal Methods: APPROVED DISPOSAL SITE I/A/W FEDERAL, STATE, LOCAL REGULATIONS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.

•



https://msdsreport.com/msds/BBFCP