

31-70015-203 POS COLOR FIXER

MSDS Number

BBFDJ

National Stock Number

6750-00D001345

Product Name

31-70015-203 POS COLOR FIXER

Manufacturer

VISUAL GRAPHICS CORP

Product Identification

Product ID:31-70015-203 POS COLOR FIXER

MSDS Date:09/01/1985

FSC:6750

NIIN:00D001345

MSDS Number: BBFDJ

Responsible Party

VISUAL GRAPHICS CORP.

5701 N.W. 94TH AVE.

TAMARAC , FL 33321

US

Emergency Phone: 305-722-3000

Cage: 26030

Contractor

VISUAL GRAPHICS CORP.

TAMARAC, FL 33321-4317

US

305-722-3000 EXT. 2299

Cage: 26030

Ingredients

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight:

AMMONIUM THIOSULFATE

CAS: 7783-18-8

RTECS: XN6465000

Fraction By Weight:

N-METHYL PYRROLIDONE

CAS: 872-50-4

RTECS: UY5790000

Fraction By Weight:

POTASSIUM SULFITE.

CAS: 10117-38-1

RTECS: WT3530000

Fraction By Weight:

POTASSIUM BISULFITE

CAS: 16731-55-8

RTECS: TT4920000

Fraction By Weight:

Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES

Effects of Overexposure:EYES:CAN CAUSE IRRITATION; SKIN:CAN CAUSE IRRITATION ON REPEATED OR PROLONGED CONTACT; ING:MAY BE HARMFUL IF SWALLOWED

First Aid

First Aid:EYES:FLUSH WITH CLEAN,WARM WATER FOR AT LEAST 15MIN & GET MEDICAL ATTENTION; SKIN:RINSE THOROUGHLY,WASH WITH MILD SOAP & WATER.REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE; ING:GIVE TWO GLASSES OF WATER.INDUCE VOMITING & CALL A PHYSICIAN.NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Fire Fighting

Extinguishing Media:USE MEDIA PROPER TO PRIMARY SOURCE OF FIRE.

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:FLUSH MATERIAL TO SEWER WITH LARGE AMOUNTS OF WATER. DISCHARGE,TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL,STATE,OR LOCAL LAWS.

Handling

Handling and Storage Precautions:AVOID REPEATED OR PROLONGED CONTACT WITH SKIN,EYES OR CLOTHING.USE WITH ADEQUATE VENTILATION.WASH THOROUGHLY AFTER HANDLING.

Exposure Controls

Respiratory Protection:NONE

Ventilation:GENERAL MECHANICAL.

Protective Gloves:SAFETY GLOVES.

Eye Protection:SAFETY GLASSES

Other Protective Equipment:RUBBER APRON.

Supplemental Safety and Health

THIS CAT#31-70015-203 IS ONLY FOR "FIXER" BY ITSELF. THE MATL CAN ALSO BE PURCHASED IN A FIVE-PART KIT,WITH MFG'S CAT#31-70000-202,REFER TO NSN 6750-01-048-3022,P-I.

Chemical Properties

HCC:N1

Boiling Pt:B.P. Text:212F/100C

Spec Gravity:>1

Evaporation Rate & Reference:SLOW

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQ, SLIGHT AMMONIA ODOR.

Percent Volatiles by Volume:25

Stability

Stability Indicator/Materials to Avoid:YES

STRONG MINERAL ACIDS.

Stability Condition to Avoid:NONE

Hazardous Decomposition Products:TOXIC SULFUR DIOXIDE FUMES.

Disposal

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE &

DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE
INTERNATIONAL, FEDERAL, STATE, & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.