

CIBACHROME-A P-30P; FIXER

MSDS Number

BBFJD

National Stock Number

6750-00D001618

Product Name

CIBACHROME-A P-30P; FIXER

Manufacturer

ILFORD PHOTO CORP

Product Identification

Product ID:CIBACHROME-A P-30P; FIXER MSDS Date: 05/11/1988 FSC:6750 NIIN:00D001618

MSDS Number: BBFJD

Responsible Party

ILFORD PHOTO CORP.

W.70 CENTURY ROAD

PARAMUS, NJ 07653

US

Emergency Phone: 800-888-8372

Info Phone: 201-265-6000

Cage: 64145

Contractor ILFORD PHOTO CORP

PARAMUS, NJ 07653

201-265-6000

US

Cage: 64145

Ingredients

AMMONIUM THIOSULFATE

CAS: 7783-18-8 RTECS: XN6465000

Fraction By Weight:

POTASSIUM SULFITE CAS: 10117-38-1

Fraction By Weight:

POTASSIUM METABISULFITE

CAS: 16731-55-8 RTECS: TT4920000 Fraction By Weight:

SODIUM THIOSULFATE

CAS: 7772-98-7



RTECS: XN6476000 Fraction By Weight:

Hazards

Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT MAY CAUSE EYE, SKIN & G/I
TRACT IRRITATION. IT IS CONSIDERED A LOW HAZARD FOR NORMAL
INDUSTRIAL HANDLING AND INHALATION IS AN UNLIKELY EXPOSURE.
Explanation of Carcinogenicity:THIS PRODUCT CONTAINS NO INGREDIENT
LISTED AS CARCINOGEN BY IARC,NTP, OR OSHA.
Effects of Overexposure:EYE:CAUSES IRRITATION SKIN:CAUSES IRRITATION.
INHALED:UNLIKELY EXPOSURE,MAY CAUSE IRRITATION IF MIST IS INHALED.
INGESTED:MAY BE HARMFUL IF SWALLOWED. HMIS:MAY CAUSE G/I
IRRITATION,NAUSEA,VOMITING.

Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER.

First Aid

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:REMOVE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE. WASH SKIN WITH SOAP AND WATER. INHALED: REMOVE TO FRESH AIR. INGESTED:DO NOT INDUCE VOMITING. IF CONSCIOUS,G IVE 1-2 GLASSES OF WATER. (NOTHING BY MOUTH IF UNCONSCIOUS.) GET IMMEDIATE MEDICAL CARE. IF ANY IRRITATION PERSISTS OR IS SEVERE, GET MEDICAL CARE.

Fire Fighting

Flash Point:>212F,>100C

Extinguishing Media: USE MEDIA APPROPRIATE FOR SOURCE OF FIRE. Fire Fighting Procedures: FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard: FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

Accidental Release

Spill Release Procedures: SWEEP UP BEING CAUTIOUS NOT TO RAISE DUST OR IF ALREADY DISSOLVED MOP UP WITH PAPER CLOTH ETC.
Neutralizing Agent: NONE

Handling

Handling and Storage Precautions:STORE IN A COOL,DRY,WELL VENTILATED AREA. KEEP TIGHTLY CLOSED WHEN NOT IN USE. KEEP AWAY FROM ACIDS AND ALKALIS.

Other Precautions: READ LABEL THEN FOLLOW INSTRUCTIONS.

Exposure Controls

Respiratory Protection: NONE NORMALLY REQUIRED. USE NIOSH/MSHA APPROVED RESPIRATOR IF PEL/TLV IS EXCEEDED OR IF LOCAL EXHAUST IS UNAVAILABLE DURING MIXING.

Ventilation: NORMAL ROOM VENTILATION IS SUFFICIENT. SUPPLEMENT WITH LOCAL EXHAUST WHEN DOING INITIAL MIXING.

Protective Gloves: RUBBER, VINYL, OTHER IMPERVIOUS Eye Protection: SAFETY GLASSES OR SPLASH GOGGLES

Other Protective Equipment: EYE WASH STATION & SAFETY SHOWER. USE APRON AND FACE SHIELD WHEN MIXING LIQUIDS OR IF SPLASHING IS LIKELY. Work Hygienic Practices: USE GOOD CHEMICAL HYGIENE PRACTICE. AVOID UNNECESSARY CONTACT.

Supplemental Safety and Health

ILFORD STOCK NUMBERS OG8250200(KIT) (MSDS DATE 23MAY88) AND OG8250320(FIXER) (MSDS DATE 11MAY88) TO MAKE 1 L. COD = 577 GM OXYGEN/KG. ALSO SEE ADD.DATA.

Chemical Properties

HCC:N1

Melt/Freeze Pt:M.P/F.P Text:>572F,>300C

Spec Gravity:POWDER



Solubility in Water:COMPLETE
Appearance and Odor:WHITE ODORLESS POWDER * PH SOLUTION = 6.8
Percent Volatiles by Volume:0

Stability

Stability Indicator/Materials to Avoid:YES STRONG ACIDS Stability Condition to Avoid:NO INFORMATION GIVEN BY MANUFACTURER Hazardous Decomposition Products:CARBON DIOXIDE, CARBON MONOXIDE, SULFUR OXIDES, AMMONIA

Disposal

Waste Disposal Methods: DISPOSE I/A/W FEDERAL, STATE, LOCAL REGULATIONS. MFR SUGGESTS FLUSH TO SEWER IF PERMITTED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.