

RUBILENE S-315:VACUUM PUMP OIL#RO-1000

MSDS Number

BBFJJ

National Stock Number

9150-00D001668

Product Name

RUBILENE S-315:VACUUM PUMP OIL#RO-1000

Manufacturer

ATLANTIC RICHFIELD COMPANY

Product Identification

Product ID: RUBILENE S-315:VACUUM PUMP OIL#RO-1000

MSDS Date: 08/01/1975

FSC: 9150

NIIN: 00D001668

MSDS Number: BBFJJ

Responsible Party

ATLANTIC RICHFIELD COMPANY

515 SOUTH FLOWER STREET

LOS ANGELES , CA 90071

US

Emergency Phone: 312-468-9300

Info Phone: 213-486-3511

Cage: 56242

Contractor

ATLANTIC RICHFIELD CO

2451

LOS ANGELES, CA 90071-2201

US

213-486-2687

Cage: 56242

Ingredients

LUBRICATING OIL

Hazards

Routes of Entry: Inhalation: YES Skin: YES Ingestion: YES

Health Hazards Acute and Chronic: ACUTE: MAY IRRITATE EYES AND SKIN OR RESPIRATORY OR G.I. TRACT IRRITATION IN FORM OF VAPORS/MIST.

CHRONIC: NO DATA AVAILABLE.

Effects of Overexposure: CONTACT OF THE OIL WITH EYES OR SKIN MAY RESULT IN SLIGHT IRRITATION.

Medical Cond Aggravated by Exposure: PRE-EXISTING CONDITIONS MAY BE WORSEN BY PROLONGED EXPOSURE.

First Aid

First Aid: EYES: WASH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES.

SKIN: REMOVE BY WIPING, WASH SKIN WITH SOAP AND PLENTY OF WATER.

INHALATION: REMOVE TO FRESH AIR. INGESTION: GIVE LARGE QUANTITIES OF WATER, INDUCE VOMITING AND GET MEDICAL ATTENTION.

Fire Fighting

Flash Point Method:COC
Flash Point:430F/221C
Autoignition Temp:Autoignition Temp Text:750F
Extinguishing Media:DRY CHEMICAL,CO*2,FOAM AND WATERFOG.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:MAY BURN, EXPLOSIVE AT HIGH TEMP;KEEP AWAY FROM HEAT AND OPEN FLAMES.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN FREE LIQUID;USE SUITABLE INERT ABSORBENT MATERIAL AND COLLECT FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT AND OPEN FLAMES.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV OR PEL.
Ventilation:LOCAL/GENERAL TO MAINTAIN ADEQUATE VENTILATION.
Protective Gloves:IMPERVIOUS
Eye Protection:CHEMICAL GOGGLES
Other Protective Equipment:FULL EYES AND SKIN PROTECTION NEEDED.
Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.DO NOT BREATHE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.
Supplemental Safety and Health

Chemical Properties

HCC:V6
Boiling Pt:B.P. Text:>600F/316C
Vapor Pres:< 0.1
Vapor Density:> 10.0
Spec Gravity:0.88
Evaporation Rate & Reference:< 1.0 (ETHER=1)
Solubility in Water:NEGLIGIBLE
Appearance and Odor:AMBER-LIQUID-LUBE OIL ODOR
Percent Volatiles by Volume:NEGLIG

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS,HYDROCARBON OILS
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:INCOMPLETE COMBUSTION MAY PRODUCE CO AND OR CO*2.

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.