01677 1677 TARO XD SAE 40;MARINE OILS

MSDS Number

BBFKJ

National Stock Number

9150-00D001720

Product Name

01677 1677 TARO XD SAE 40;MARINE OILS

Manufacturer

TEXACO INC CORPORATE H Q

Product Identification

Product ID:01677 1677 TARO XD SAE 40;MARINE OILS
MSDS Date:09/29/1986
FSC:9150
NIIN:00D001720
MSDS Number: BBFKJ

Responsible Party

TEXACO INC. CORPORATE H.Q.

2000 WESTCHESTER AVE

WHITE PLAINS , NY 10604

US

Emergency Phone: 914-831-3400 EXT.204

Info Phone: 914-831-3400 EXT.204

Preparer: R.T.RICHARDS

Cage: EO112

Contractor

TEXACO INC. CORPORATE H.Q.

WHITE PLAINS, NY 10604

US

914-831-3400 EXT.204

Cage: EO112

Ingredients

CALCIUM PHENATE IN HIGHLY REFINED,SEVERELY HYDROTREATED

CAS: 64742-54-7

RTECS: PY8035500

Fraction By Weight: 4-11%

SOLVENT-DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATES

CAS: 64742-65-0

RTECS: PY8038500

Fraction By Weight: 80-95%

Hazards

LD50 LC50 Mixture:LD 50 >5G/KG RAT;DERMAL >3G/KG RABBIT
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:MINIMALLY IRRITATING TO EYES,SKIN AND RESPIRATORY AND G.I.TRACTS. CHRONIC:NOT KNOWN;USED OIL MIGHT BE VERY TOXIC;USE REASONABLE CARE PARTICULARLY SKIN CONTACT.
Effects of Overexposure:MAY IRRITATE EYES,SKIN,RESPIRATORY OR G.I.TRACTS. USE REASONABLE CARE.AVOID SKIN CONTACT.
Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN.

First Aid

First Aid:EYES:FLUSH WITH PLENTY OF WATER FOR 15 MINUTES;GET MEDICAL ATTENTION. SKIN:WASH THOROUGHLY WITH SOAP AND WATER. INHALATION:REMOVE TO FRESH AIR.

Fire Fighting

Flash Point Method:COC
Flash Point:440F/227C
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL,WATER SPRAY.
Fire Fighting Procedures:WEAR NIOSH/MSHA APPROVED SCBA IN AN ENCLOSED AREA.
Unusual Fire/Explosion Hazard:NONE NOTED;MAY GIVE COMBUSTION PRODUCTS OF C,S,N.

Accidental Release

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT,OPEN FLAMES & SPARKS.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR OIL MIST IF ABOVE TLV/PEL.
Ventilation:GENERAL/LOCAL TO MAINTAIN ADEQUATE VENTILATION.
Protective Gloves:IMPERVIOUS
Eye Protection:CHEMICAL GOGGLES/FACE SHIELD
Other Protective Equipment:FULL SKIN AND EYES PROTECTION;EYE WASH,SAFETY SHOWER.
Work Hygienic Practices:AVOID CONTACT WITH SKIN AND EYES;DO NOT BREATHE VAPORS/FUMES;WASH THOROUGHLY AFTER EACH USE.
Supplemental Safety and Health

Chemical Properties

HCC:V6
Spec Gravity:0.90
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK RED

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS.
Stability Condition to Avoid:EXTREME HEAT
Hazardous Decomposition Products:CO,CO*2,ALDEHYDES,KETONES,COMBUSTION PRODUCTS OF N,S.

Disposal

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.